

Extra Smooth Acceleration & Broad Power

Balanced Chassis for Comfort & Performance

Stylish Half-fairing Reduces Wind Buffeting

Anti-lock Brake System (ABS)

Adjustable Seat Height & Standard Center Stand

NEW
FOR 16



BANDIT 1250S ABS COLORS



Candy Daring Red



Glass Sparkle Black

2016

Bandit S
1250 ABS

SUZUKI

NEW
FOR 2016

You can't break the laws of physics, but the 2016 Suzuki Bandit 1250S ABS shows that you sure can bend them. Its Suzuki fuel-injected four-cylinder engine offers thrilling acceleration in every gear, with a rush of high-rpm performance. For crisp, precise handling on twisty roads, it has balanced suspension systems front and rear. It also features a technically advanced Antilock Braking System (ABS)* that monitors wheel speed, and matches stopping power to available traction.

BANDIT 1250S ABS FEATURES

- Powering the Bandit S is a 1,255cc liquid-cooled, DOHC, four-cylinder engine delivering a wide spread of power for relaxed cruising or sport riding.
- Engineered for smooth operation, the engine has an effective secondary balancer shaft.
- Power is transmitted through a 6-speed transmission using gear ratios chosen for impressive accelerations as well as smooth highway use. Clutch operation is low effort and smooth, with low maintenance, thanks to a hydraulic clutch actuation system.
- The state-of-the-art Suzuki Dual Throttle Valve (SDTV) digital closed-loop EFI system delivers improved mileage and reduced emissions.
- The 4-into-2-into-1 exhaust system is built of steel and stainless steel and is equipped with a catalyzer and HO2 sensor. The large silencer controls sounds while permitting excellent flow to maximize torque and overall engine power.
- To shed heat from the high torque, large displacement engine, a high capacity radiator is employed. Cooling air is directed to the radiator via the front fender and then warm air is directed away by the outer fairing shroud.
- Additional engine cooling comes from a compact liquid-cooled oil cooler, similar to the type used on the GSX-R750
- The refined half-fairing wraps around the radiator sides and is vented just below the headlight. In addition to sharpening the Bandit's looks, the fairing improves aerodynamics providing riders with great wind protection and riding comfort.
- Hollow, three-spoke cast wheels feature 1270/70ZR17 and 180/55ZR17 radial tires.
- The strong, double-cradle steel frame supports a stout set of SHOWA 43mm forks with adjustable spring preload.
- The single rear shock that works with a progressive, rising rate link system designed to respond smoothly to road irregularities. Rear shock rebound damping and spring preload are adjustable.
- Stopping power is provided by fully floating 310mm-diameter dual front brake discs with 4 piston calipers and a 240mm diameter rear disc brake with a single piston caliper.
- The standard digital ABS monitors wheel speed, matching stopping power to available traction*.
- The analog tachometer on the left side of the instrument panel incorporates FI and ABS indicators.
- The LCD panel on the right side displays a digital speedometer and odometer, dual trip meters, clock, and a fuel gauge.
- The height of the comfortably contoured seat can be adjusted up or down by 20mm (0.78 in.).
- The passenger grab bar incorporates cargo cord posts.
- A convenient center stand is standard.
- For Genuine Suzuki Accessories, please visit store.suzukicycles.com for availability.
- 12-month limited warranty
- For more details, please visit www.suzukicycles.com.

* Depending on road surface conditions, such as wet, loose, or uneven roads, braking distance for an ABS-equipped vehicle may be longer than for a vehicle not equipped with ABS. ABS cannot prevent wheel skidding caused by braking while cornering. Please ride carefully and do not overly rely on ABS.



BANDIT 1250S ABS SPECIFICATIONS

Engine	1255cc, 4-cylinder, 4-stroke, DOHC
Fuel System	Suzuki fuel injection
Ignition	Electronic ignition (transistorized)
Starter	Electric
Transmission	6-speed constant mesh
Final Drive	O-ring type, sealed drive chain
Suspension Front	Telescopic, coil spring, oil damped (SHOWA)
Suspension Rear	Single shock, coil over damper, link-style (SHOWA)
Brakes Front	Disc brake, twin
Brakes Rear	Disc brake,

Tires Front	120/70ZR-17M/C (58W), tubeless
Tires Rear	180/55ZR-17M/C (73W), tubeless
Overall Length	2130 mm (83.9 in)
Overall Width	790 mm (31.1 in)
Wheelbase	1485 mm (58.5 in)
Ground Clearance	135 mm (5.3 in)
Seat Height	LOW: 805 mm (31.7 in), HIGH: 825 mm (32.5 in)
Curb Weight	254 kg (560 lbs)
Fuel Tank Capacity	19.0 L (5.0 US gal)

Suzuki Motor of America, Inc. makes every effort to present the most current specifications and product features at the time of publication. Because of our policy of continual improvement, changes may be made in equipment, availability and specifications without notice or obligation. At Suzuki, we want every ride to be safe and enjoyable. So always wear a helmet, eye protection and protective clothing. Never ride under the influence of alcohol or other drugs. Never engage in stunt riding. Avoid excessive speeds. Study your owner's manual and always inspect your Suzuki before riding. Take an MSF skills course, for the street course nearest you call 1-800-446-9227. Limited Warranty: The 2016 Bandit 1250S ABS limited warranty covers a period of 12 months. See your dealer for details. Ask your participating dealer about Genuine Suzuki Accessories and the Suzuki Retail Finance Plan and the Suzuki Extended Protection Plan. With the Suzuki Retail Finance Plan it's easy to afford and equip the machine that's perfect for you. VISIT SUZUKICYCLES.COM FOR MORE INFORMATION. Suzuki, the "S" logo, and Suzuki model and product names are Suzuki Trademarks or ®. © Suzuki Motor of America, Inc. 2015