

84.7cc, 2-stroke, liquid-cooled, single cylinder produces smooth power at any RPM

Smooth 6-speed transmission with precise shifting and clutch action to blast out of any corner

Class-leading lightweight handling

Fully tunable SHOWA suspension

Champion Approved RM-Z styling



RM85 COLORS



Champion Yellow No. 2 / Solid Black

The 2016 Suzuki RM85 carries on the Suzuki RM tradition of racing excellence. Just like the larger models, the RM85 delivers class-leading handling for both experienced racers and rookie riders alike. With the strong, smooth power delivery of its two-stroke engine, complemented by lightweight handling, the RM85 is the perfect motocross bike for anyone learning to race – and striving to win!

RM85 FEATURES

- The high-revving 84.7cc, 2-stroke, liquid-cooled, reed-valve, single-cylinder engine has a bore and stroke of 48.0 x 46.8mm.
- The cylinder features Suzuki Composite Electrochemical Material (SCEM) for durability, low weight and effective heat transfer for superior class performance.
- The exhaust valves are made of aluminum to best match the expansion rate of the cylinder, improving sealing for better engine performance.
- The exhaust valve governor and actuator help provide good throttle response and overall tractability.
- Precise Keihin™ PE28 carburetor provides smooth throttle response, and is designed for simplified maintenance and tuning.
- Digital CDI mapping helps create strong engine performance at high RPM.
- The large-capacity radiator provides efficient engine cooling at all engine speeds.
- The RM85 is equipped with a smooth shifting six-speed transmission plus a precise rack and pinion activated clutch.
- The long clutch lever makes it easy to accurately locate and work the engagement point during starts and driving off of corners.
- This durable transmission features a refined shift mechanism with a strong detent spring and needle bearing on the left side of the shift drum.
- A knurled shift-pedal tip delivers excellent grip and shift feel for precise gear selection.
- A tubular steel frame with aluminum beam swingarm provide class-leading performance on the track, especially in the corners. Designed for rigidity, durability and straight-line performance, the frame features large diameter tubing in key areas and a large front reinforcement plate.
- SHOWA 37mm inverted front forks are completely adjustable for rider weight, style and ability. The forks feature a cartridge system with fully-adjustable rebound damping and 20-way adjustable compression damping (also included are guards to protect the inner fork tubes). The forks have 275mm (10.8-inches) of travel.
- A SHOWA large diameter rear shock absorber is valved to produce a plush feel and resistance to bottoming. The shock provides 277mm (10.9-inches) of wheel travel and features adjustable compression and rebound damping force adjustment.
- A twin-piston caliper front brake with 220mm (8.7-inches) large-diameter disc and a rear brake with 200mm (7.9-inches) disc to provide excellent braking performance.
- The light, narrow-diameter front and rear brake hoses improve feel and feedback to the rider. The front hose is routed behind the fork leg, eliminating the need for a brake hose cover.
- A rigid rear brake caliper provides reliable braking performance, long pad life and is easy to maintain. The caliper's plastic guard reduces the possibility of damage and saves weight.
- High-quality footpegs are made of cast chrome-molybdenum steel, instead of stamped steel, which makes them more durable with better grip.
- Revised graphics with Champion Yellow bodywork plus new black protectors and guards provide a professional race look.
- Each side of the seat has textured surface for better knee gripping.
- The RM85's wheel sizes meet AMA 85cc class regulations (Front: 70/100-17; Rear: 90/100-14).
- See Suzuki's industry leading Amateur Contingency program at www.SuzukiCycles.com/Racing.
- For more details, please visit www.suzukicycles.com.



RM85 SPECIFICATIONS

Engine	84.7cc, 2-stroke, liquid-cooled, single cylinder
Fuel System	KEIHIN PE28, single
Ignition	Electronic ignition (CDI)
Starter	Primary kick
Transmission	6-speed constant mesh
Final Drive	Chain, DID428DS, 118 links
Suspension Front	Telescopic, pneumatic/coil spring, oil damped
Suspension Rear	Link type, coil spring, oil damped
Brakes Front	Disc brake
Brakes Rear	Disc brake

Tires Front	70/100-17 40M, tube type
Tires Rear	90/100-14 49M, tube type
Overall Length	1805 mm (71.1 in)
Overall Width	735 mm (28.9 in)
Wheelbase	1240 mm (48.8 in)
Ground Clearance	325 mm (12.8 in)
Seat Height	850 mm (33.5 in)
Curb Weight	73 kg (161 lbs)
Fuel Tank Capacity	5.0 L (1.3 US gal)

Suzuki Motor of America, Inc. makes every effort to present the most current specifications and product features at the time of publication. Because of our policy of continual improvement, changes may be made in equipment, availability and specifications without notice or obligation. At Suzuki, we want every ride to be safe and enjoyable. Always wear a helmet, eye protection and protective clothing. Never ride Under the Influence. Inspect your Suzuki before riding. Always supervise young riders. The RM and RM-Z series motorcycles are for closed-course competition and related practices only. Take an MSF skills course. For the street course nearest you call 1-800-446-9227. For the MSF DirtBike SchoolSM call 1-877-288-7093. Along with concerned conservationists everywhere, Suzuki urges you to Treat Lightly® on public and private land. Preserve your future riding opportunities by showing respect for the environment, local laws and the rights of others when you ride. Ask your participating dealer about Genuine Suzuki Accessories and the Suzuki Retail Finance Plan and the Suzuki Extended Protection Plan. With the Suzuki Retail Finance Plan it's easy to afford and equip the machine that's perfect for you. VISIT SUZUKICYCLES.COM FOR MORE INFORMATION. Suzuki Motor of America, Inc., 3251 East Imperial Highway, P.O. Box 1100, Brea, CA 92822-1100, Suzuki, the "S" logo, and Suzuki model names are Suzuki trademarks or ®. ©Suzuki Motor of America, Inc. 2015