ZIR 6505



644cc, 4-stroke, air-cooled, single cylinder, OHC

Ready to cruise around town, up the highway, or your favorite trail

Convenient electric starter

Adjustable Seat Height

SUZUKI



DR650S COLORS



Solid Black



The 2017 Suzuki DR650S is quite possible the best, all-around dual purpose motorcycle available today. Every DR650S is quality-built by Suzuki and features a reliable 644cc oil-cooled four-stroke single carried in a strong, steel semi-double cradle frame. The cartridge-style fork and link-style rear suspension can tackle tough trails or urban roads. So a variety of riders can enjoy this motorcycle, the seat height can be significantly reduced. Strong aluminum, spoke-style rims carrying tires that can handle the street or dirt are fitted so riders can tackle pavement or soil with ease. With new black bodywork and distinctive graphics, the DR650S will look good on any surface it's ridden on.

DR650S FEATURES

- The compact and powerful 644cc, SOHC, four-stroke, air & oil-cooled, engine features the Suzuki Advanced Cooling System (SACS). Piston-jet cooling and an engine oil cooler create consistent performance in a variety of conditions.
- The engine is tuned with an emphasis on performance in the low-to-mid RPM range, while a gear-driven counter balancer minimizes vibration for comfortable ride.
- Suzuki Composite Electrochemical Material (SCEM) coated aluminum cylinder is used for durability, light weight and excellent heat dissipation.
- Digitally mapped DC-CDI ignition system provides accurate spark timing for efficient combustion.
- A convenient electric starter (supplemented with a zero-maintenance automatic decompression system) provides easy, quick starting.
- Large MIKUNI 40mm (1.6 in) carburetor provides a smooth intake flow and quick throttle response.
- The stainless-steel exhaust system is light and corrosion-resistant, and is tuned specifically for strong low and midrange power.
- Easy-pull rack and pinion activated clutch proves precise operation and feel.
- A smooth-shifting 5-speed transmission is complemented by a sealed 0-ring drive chain.
- A lightweight, compact, rigid semi-double cradle frame provides agile handling on and off road.
- Innovative, height-adjustable* front forks provide smooth and progressive action. Large diameter, thin-walled tubes reduce unsprung weight while maintaining high rigidity.
- Front and rear suspensions provides generous 260mm (10.2-inch) wheel travel for superb performance over rough terrain.

- A link-type rear suspension with piggyback-style aluminum-body shock absorber provides stable performance. The height adjustable* shock features adjustable spring preload and compression damping to personalize the suspension for rider, load and terrain.
- Lightweight 290mm (11.4-inch) front floating disc brake with two-piston caliper and 240mm (9.4-inch) rear disc brake with two-piston caliper provide reliable stopping power.
- · Aluminum rims with stainless steel spokes are standard.
- The wheels are fitted with 90/90-21 front and 120/90-17 rear tires that offer excellent on and off road traction.
- Hollow-type wheel axles and an aluminum, beam-style swingarm reduce unsprung weight.
- A long, comfortable seat, aluminum footpegs and grab handles allow you to carry a passenger with ease.
- Powered by a lightweight and compact low-maintenance battery.
- A fully equipped lighting system comes with a bright 60/55W halogen headlight.
- Seat height may be lowered by 40mm (1.6 in) using a Genuine Suzuki Accessory kit. The kit includes a shorter side stand to match the chassis height adjustment.
- Other Genuine Suzuki Accessories include a low profile seat, cargo rack, skid plate and more.
- 12-month limited warranty
- For more details, please visit www.suzukicycles.com.

DR650S SPECIFICATIONS

| 644cc, 4-stroke, air-cooled, single cylinder, OHC |
|---|
| MIKUNI BST40, single |
| Electronic ignition (CDI) |
| Electric |
| 5-speed constant mesh |
| Chain, DID525V9, 110 links |
| Telescopic, coil spring, oil damped |
| Link type, coil spring, oil damped |
| Disc brake |
| Disc brake |
| |

| Tires Front | 90/90-21M/C 54S, tube type |
|-------------------------|--|
| Tires Rear | 120/90-17M/C 64S, tube type |
| Overall Length | 2255 mm (88.8 in), Low: 2235 (88.0 in) |
| Overall Width | 865 mm (34.1 in) |
| Wheelbase | 1490 mm (58.7 in), Low: 1475 mm (58.1 in) |
| Ground Clearance | 265 mm (10.4 in), Low: 225 mm (8.9 in) |
| Seat Height | 885 mm (34.8 in), Low: 845 mm (33.2 in) |
| Curb Weight | 166 kg (366 lbs) |
| Fuel Tank Capacity | 13.0 L (3.4 US gal), CA model: 12.0 L (3.2 US gal) |

Suzuki Motor of America, Inc. makes every effort to present the most current specifications and product features at the time of publication. Because of our policy of continual improvement, changes may be made in equipment, availability and specifications without notice or obligation. At Suzuki, we want every ride to be safe and enjoyable. So always wear a helmet, eye protection and protective clothing. Never ride under the influence of alcohol or other drugs. Study your owner's manual and always inspect your Suzuki before riding. Take an MSF skills course, for the street course nearest you call 1-800-446-9227. Along with concerned conservationists everywhere, Suzuki urges you to Tread Lightly!® on public and private land. Preserve your future riding opportunities by showing respect for the environment, local laws and the rights of others when you ride. Limited Warranty: The 2017 DR650S limited warranty covers a period of 12 months. See your dealer for details. Ask your participating dealer about Genuine Suzuki Accessories and the Suzuki Retail Finance Plan and the Suzuki Thance Plan it's easy to afford and equip the machine that's perfect for you. VISIT SUZUKICYCLES.COM FOR MORE INFORMATION. Suzuki, the "S" logo, and Suzuki model and product names are Suzuki Trademarks or ®. @ Suzuki Motor of America, Inc. 2018.

^{*}Seat and suspension height is adjustable by your Suzuki Dealer using a Genuine Suzuki Accessory kit.