

SUZUKI

SUZUKI
KINGQUAD

750AXi
4x4
POWER STEERING

2017

722cc, DOHC, single-cylinder, liquid-cooled, four-stroke engine

QuadMatic™ CVT-type automatic transmission with advanced engine-braking system

Compact and lightweight advanced electric power steering system

Dual hydraulic front disc brakes plus a sealed, multi-plate rear brake system

Special oversize front and rear bumpers, plus front and rear flared mud guards

Rugged Package



KINGQUAD 750AXi POWER STEERING COLORS



Solid Matte Sword Black
"Special Edition w/ Rugged Package"

This exceptional four-wheeler boasts the same advanced technology as the 2017 KingQuad 750AXi Power Steering; Suzuki's most powerful and innovative ATV. With new, beefy bumpers and wide, protective mud flaps it's engineered to help you tackle tough trails and tougher jobs. Abundant torque developed by the 722cc fuel-injected engine provides performance that's the standard for Utility Sport ATVs. The advanced Power Steering system provides responsive handling, reduces turning effort, and damps vibration to the rider. The KingQuad's easily adjustable suspension lets you float over rough obstacles with ease while still being able to haul or tow what you need to get the job done.

KINGQUAD 750AXi POWER STEERING FEATURES

- Advanced electric power steering provides the KingQuad 750AXi with light steering and responsive handling. The system also permits the use of higher handle bars for more rider comfort.
- The powerful 722cc, SOHC, single-cylinder, liquid-cooled, four-stroke engine produces a wide powerband with strong top-end power.
- Precise Suzuki fuel injection system and twin iridium spark plugs ensure easy starting, excellent throttle response, great fuel efficiency, and reduced emissions.
- Its cylinder is canted forward for a low center of gravity resulting in reduced engine height and lower seat height. The engine also features a counterbalancer shaft for smooth operation.
- The compact 4-valve cylinder head has large intake valves and straight intake ports for superb cylinder charging efficiency.
- A lightweight aluminum cylinder uses SCEM (Suzuki Composite Electrochemical Material) coating for excellent heat transfer and ring sealing resulting in superb combustion chamber efficiency.
- High capacity aluminum radiator with large diameter, thermostatically controlled cooling fan provides stable engine operating temperature.
- The QuadMatic™ CVT-type automatic transmission provides versatility and convenience with a fender-mounted gate-type shifter for high/low range selection. Its advanced engine-braking system minimizes free-wheeling with the throttle off and helps control the vehicle during steep descents.
- A compact torque-sensing limited-slip front differential offers potent traction augmented by the Power Steering system. A differential-lock system provides serious four-wheel-drive traction.
- Handlebar-mounted push-button controls permit easy selection between 2WD, 4WD and differential-lock 4WD. An override button on the left handlebar can be used to override the normal speed limiter when stuck in the mud.
- Stylish bodywork features high-clearance fenders equipped with wide, flared mud guards that offer great protection for the rider from flying debris. Carefully designed body panels simplify maintenance needs, such as oil level checks.
- Independent double A-arm front suspension (6.7 inches of wheel travel) includes large diameter shock absorbers with 5-way spring preload adjustment.
- Fully independent, A-arm/I-beam rear suspension with 7.7 inches of wheel travel includes large diameter shock absorbers with 5-way spring preload adjustment and large diameter rear sway-bar.
- Dual hydraulic front disc brakes plus a sealed, multi-plate rear brake system. The rear brake's clutch-type design provides high durability, reduced unsprung weight, and low-maintenance.
- High traction 25-inch CARLISLE tires are mounted on lightweight and strong aluminum wheels.
- Suzuki's plush T-shaped seat delivers rider mobility during spirited or difficult terrain riding.
- Polyethylene skid plates provide protection with minimal resistance over rocks and rough terrain. Durable plastic guards protect the front and rear half shafts.
- Large diameter, oversize bumpers are mounted to the front and rear for maximum protection and utility. The rear bumper features a square hitch receiver that lets you take advantage of the ATV's strong towing capacity.
- Dual 35W headlights (with high and low settings) are part of the distinctive KINGQUAD grille appearance. Bright tail light help make the ATV visible in dark conditions.
- Winch-ready mounts and wire conduit make winch installation simple.
- Instrumentation includes LCD readouts for speedometer, odometer, twin tripmeter, hour meter, clock, fuel level, driving range, and drive mode. LED indicators for high, low, neutral, reverse, 2WD/4WD, and differential-locked 4WD. LED cautions for fuel injection and engine temperature.
- High-output, three-phase charging system feeds an 18-amp maintenance-free battery for abundant power for easy starting and accessory use.
- The large 4.6 gallon (17.5 L) fuel tank is positioned for a low center-of-gravity. It includes a vacuum-operated petcock and a ratchet-style filler cap.
- A large 2.8 liter water resistant front storage compartment includes an easy access screw-on cap.
- The rugged steel-tube cargo racks have wrinkle paint finish for durability and scratch resistance.
- A variety of Suzuki Genuine Accessories are available including winches, windshield, snow plow, aluminum skid pans, rack extensions, utility box and more.
- 12-month limited warranty.
- For more details, please visit www.suzukicycles.com.

KINGQUAD 750AXi POWER STEERING SPECIFICATIONS

Engine	722cc, 4-stroke, liquid-cooled, SOHC
Fuel System	Suzuki fuel injection
Ignition	Electronic ignition (CDI)
Starter	Electric
Transmission	Automatic variable ratio (V-belt), with high-/low-range, and reverse
Final Drive	Shaft drive
Suspension Front	Independent, double wishbone, coil spring, oil damped with five-way preload adjustable shock absorbers
Suspension Rear	Independent, double wishbone, coil spring, oil damped with five-way preload adjustable shock absorbers
Brakes Front	Disc brake, twin

Brakes Rear	Sealed oil-bathed multi-disc
Tires Front	AT25 × 8-12, tubeless
Tires Rear	AT25 × 10-12, tubeless
Overall Length	2115 mm (83.3 in)
Overall Width	1210 mm (47.6 in)
Wheelbase	1285 mm (50.6 in)
Ground Clearance	260 mm (10.2 in)
Seat Height	920 mm (36.2 in)
Curb Weight	305 kg (672 lbs) <i>*Does not include mounted accessories</i>
Fuel Tank Capacity	17.5 L (4.6 US gal)