

2018

GSX-R1000
ABS



- DOHC inline-4 engine produces great top-end power with a strong low- to mid-range pull thanks to the exclusive Suzuki Variable Valve Timing system
- Advanced electronics include an Inertia Measurement Unit, S-DMS adjustable engine output, and Traction Control to increase track and street performance
- Twin-spar-type aluminum frame is lighter and more compact than the prior GSX-R1000 for nimble handling with a high level of grip when cornering
- Advanced Showa suspension combines with ABS-equipped Brembo T-drive front brake rotors and 4-piston calipers for extraordinary handling and stopping performance
- Aerodynamic fairing houses a bright LED headlight and Suzuki Ram Air Direct ducts that feed the engine to boost top-end power



GSX-R1000 ABS COLORS



Pearl Glacier White



Metallic Matte Black No. 2

2018

GSX-R1000 ABS



It has been three decades, with more than a million editions sold, since the GSX-R line was born. And a decade and a half has elapsed since the first GSX-R1000 transformed the open sportbike class forever. Built to own the racetrack, the GSX-R1000 captured the MotoAmerica Superbike Championship in its debut year asserting its claim as the king of sportbikes.

This motorcycle's chassis forms the lightest, the most compact, the most aerodynamic, and the best-handling GSX-R1000 ever. Cradled in this aluminum frame is an advanced engine that uses an exclusive Variable Valve Timing system and Ride-by-Wire throttle bodies for a wide spread of power while delivering smooth and precise throttle response.

Using an Inertial Measuring Unit (IMU) the GSX-R1000 ABS's advanced electronics package includes selectable performance modes so the motorcycle enhances and fine tunes rider inputs. The 6-axis IMU lets the GSX-R1000 ABS recognize its position on the street or racetrack to help the rider achieve an extraordinary level of riding performance.

Up front, the unique Brembo T-drive brake rotors are grasped by monobloc calipers connected to the exclusive Suzuki Motion Track Anti-lock Brake System providing strong, controlled braking. The precise and smooth Showa suspension keeps the sticky Bridgestone RS10 tires in touch with the road. All of this forward-looking motorcycle technology is covered in sleek, wind tunnel-developed bodywork that's uniquely GSX-R.

GSX-R1000 ABS FEATURES

ADVANCED ELECTRONICS FEATURES

- A powerful 32-bit Dual Processor Engine Control Module (ECM) blends Suzuki's vast street-going EFI knowledge with the intelligence from Suzuki's race-winning MotoGP program. GSX-R1000 ABS riders will get sportbike performance without peer while simultaneously receiving polished street manners.
- Using MotoGP knowledge, Suzuki has fitted an Inertial Measurement Unit (IMU) to the GSX-R1000 ABS. The IMU provides 6-direction, 3-axis motion and position information to the ECM so instantaneous adjustments can be made electronically to the engine and chassis components that influence performance.
- The LCD Multifunction Instrument Panel was inspired by the GSX-RR MotoGP dash. This panel is laid out so the rider can easily see the tachometer bar, speedometer digits, and other essential operational information. This effective display is critical as it is the rider's interface to the GSX-R1000 ABS's advanced electronics.
- Ride-by-Wire electronic throttle bodies are precisely opened by the ECM to match the throttle grip rotation of the rider's hand and the refinement from the IMU-influenced electronics. The result is a strong, seamless engine power delivery from idle to redline.
- The 3-mode Suzuki Drive Mode Selector (S-DMS) system lets the rider select the power output levels of the engine to match riding ability and conditions.
- The exclusive 10-mode Motion Track Traction Control System (MT-TCS), with IMU influence, increases rider confidence by allowing adjustments to the amount of intervention to match riding ability and surface conditions.
- Exclusive to Suzuki, the new Motion Track Anti-lock Brake System (ABS) brings additional control to anti-lock braking. Like a conventional Anti-lock Brake System, the Motion Track Brake System provides the appropriate amount of braking force for the available traction. When the IMU detects the rear wheel lifting up from extreme braking forces, the ABS control module will adjust the front brake pressure to reduce the rear wheel lift.
- The Suzuki Easy Start System simplifies start-up for the GSX-R1000 ABS rider as the ECM automatically cranks the engine for 1.5 seconds (or until it starts) with a momentary press of the starter button. There is no need to pull in the clutch lever if the transmission is in neutral. Once started, the ECM will control the electronic throttle bodies to maintain a consistent engine idle speed, whether the engine is cold or warm.
- The innovative Suzuki Low RPM Assist System smooths take-offs and reduces the chance of the rider stalling the motorcycle. If necessary, the ECM raises engine RPM slightly for a smoother start when the clutch is released so it's easier to ride away from a stop or navigate at very low speeds in traffic.

ENGINE FEATURES

- The compact, 4-stroke, liquid-cooled, DOHC, 999.8cc inline-4-cylinder engine is designed with a high level of top-end performance plus strong low- to mid-range power.
- The crankshaft retains Suzuki's Even Firing Order Engine legacy. Uneven firing order engines used in other motorcycles vibrate more, while the GSX-R1000 ABS makes good power at all engine speeds and runs smoother and more reliably while emitting a screamer exhaust note.
- The short-stroke engine has a 76.0 mm bore versus a 55.1 mm stroke yet is narrower than the prior generation GSX-R1000 thanks to effective design.
- The engine has been rotated back and positioned in the frame to create optimal chassis dimensions for precise handling and to balance the motorcycle's weight.
- The exclusive Suzuki Racing Variable Valve Timing System (SR-VVT) uses a centrifugal actuated mechanism on the intake camshaft sprocket to increase high engine RPM power without losing low- to mid-range power.
- The Suzuki Racing Finger Follower valve train weighs less than a tappet-style valve train for reduced friction and increased valve response at higher engine speeds.
- Titanium valves – two 31.5 mm intake and two 24 mm exhaust valves – are used for each cylinder. The lighter valves respond well to the finger follower's arms and permit a 14,500 RPM redline that helps produce very high peak horsepower.
- Aluminum pistons, 76.0 mm in diameter, were engineered with the use of FEM (Finite Element Method) analysis, and are cast for optimal rigidity and weight.
- Suzuki Composite Electrochemical Material (SCEM) coated cylinders are integrated into the upper crankcase to reduce friction and improve heat transfer and durability.
- The high 13.2:1 compression ratio helps produce high horsepower. The cylinder head's shallow combustion chamber minimizes heat produced during operation.
- The EFI system uses Suzuki's Ride-by-Wire Electronic Throttle Bodies where the throttle valves are controlled by a servo motor for fast response to rider throttle grip input while delivering precise and smooth power delivery.
- The automatic Idle Speed Control (ISC) improves cold starting and stabilizes the engine idle regardless of engine temperature.
- Complementing the four primary fuel injectors in the throttle bodies are four Suzuki Top Feed Injectors (S-TFI) that spray fuel from the top of the air box directly into the intake funnels. This results in higher peak power, more efficient combustion, and a higher level of fueling control.
- To increase top-end power without losing lower RPM performance, the air box is equipped with Staked Air Intake Funnels for the #1 and #4 cylinders. This simple design allows good air flow at all intake speeds without requiring a mechanism that adds weight or complexity.
- A pair of Suzuki Ram Air Direct (SRAD) intake ducts are used to exponentially increase the volumetric flow of air amount coming in the air box as road speed increases.
- The digital ignition fires iridium-type spark plugs that increase spark strength and combustion efficiency. These quality components also last longer than conventional spark plugs.
- The 4-2-1 exhaust system with titanium muffler is designed help the engine deliver a wide range of performance with an exciting rush up to redline.
- The Suzuki Exhaust Tuning (SET) system valve in the mid-pipe helps control back-pressure and flow to the muffler to widen power delivery and reduce exhaust sounds without needing a larger silencer.
- SET-Alpha exhaust valves in the balance tubes between the #1 and #4, and the #2 and #3 head pipes open at higher engine speeds and close at lower RPM to help the engine create high peak power without losing low- and mid-range horsepower.
- The titanium muffler has a pleasing appearance while creating an exciting, distinctive sound.
- The cooling system was designed using advanced analysis design so the coolant flows through the engine and radiator more efficiently. This design uses 400cc less coolant than the prior generation GSX-R1000, but the new system has better cooling efficiency while being more compact and lighter.

2018

GSX-R1000 ABS



GSX-R1000 ABS FEATURES

- The fairing lowers efficiently guide cooling air to the high-capacity curved radiator. Twin cooling fans ensure good cooling at lower road speeds.
- Additional heat is removed from the engine via the use of an air-cooled, radiator-style oil cooler mounted directly below the main radiator.

TRANSMISSION FEATURES

- The cassette-style, 6-speed transmission lets riders precisely match the gear ratio to the riding condition. A cassette-style transmission can be easily removed from the crankcase as an assembly with the engine still in the frame, facilitating racetrack gear changes and simplified service.
- Based on Suzuki's race-proven close-ratio transmissions, the GSX-R1000 ABS employs vertically staggered shafts to reduce overall engine length.
- The primary gear ratio is lower compared to the prior generation GSX-R1000 for stronger acceleration.
- The shift linkage can be easily set up for reverse pattern, GP-style shifting.
- A programmable shift light is on the main panel to provide a visual alert to the rider to shift when a certain engine RPM is reached.
- A Suzuki Clutch Assist System (SCAS) multi-plate, wet clutch modulates engine power to the drive train. SCAS works like a slipper clutch during downshifts, while increasing pressure on the plates during acceleration. This smooths engine braking and lightens the clutch lever pull.
- To reduce weight, a 525-size drive chain is used with a 45/17 final sprocket ratio to complement the larger rear-tire dimensions.

CHASSIS FEATURES

- Using lessons learned from Suzuki MotoGP chassis development, the engine angle of the GSX-R1000 ABS was rotated backwards 6 degrees. This had the joint effect of reducing the distance of the fork to the center of the chassis by 20 mm and increasing the swingarm length by 40 mm. This increases chassis stability and improves aerodynamics.
- The aluminum twin-spar-style frame was designed using FEM analysis technology to place strength in the proper places; the new frame is also 10% lighter than the prior generation GSX-R1000. The spars of the frame are set 20 mm closer to help improve aerodynamics and looks and to bring more comfort to the rider.
- The aluminum Superbike-braced swingarm has equalized bracing to the main beams to provide balanced support and movement to the shock absorber to improve racetrack handling while conveying a consistent suspension feel to the rider.
- Racetrack-developed links connect the single Showa Remote Reservoir Shock Absorber to the braced swingarm. With spring preload, rebound damping, plus high- and low-speed compression damping force adjustment the rider can tune the motorcycle to respond to riding style and weight.
- Superb suspension action is delivered by the fully adjustable Showa Big Piston Fork (BPF), which is renowned for damping force control that maintains front tire contact with the surface so the rider gets good sensory feedback while riding at a variety of speeds.
- Brembo Radial Mount Brake Calipers provide the rider with strong braking performance combined with superb feel.
- Brembo T-drive Brake Rotors feature two methods of attaching the 320 mm floating disc to the carrier. There are five conventional floating rotor spools that maintain the rotor's relationship to the caliper and five new-design T-drive fasteners. This combed attachment technique allows the rotor to absorb more energy so a high degree of braking force is available to a GSX-R1000 ABS rider.
- The front brakes are complemented by a 240 mm rear disc brake with a Nissin single-piston caliper to help make sure you have controlled stops.
- Exclusive to Suzuki, the lightweight 6-spoke wheels reduce unsprung mass and have been designed to handle the braking and drive forces that a GSX-R1000 ABS can create.
- The wheel rims have pinstripes punctuated by "R" logos that highlight the bike's identity.

- The track-day-ready Bridgestone RS10 low-mass tires, with a new, 55% higher profile in the back, are premium high-grip radials that achieve excellent handling and stability.
- The aerodynamic bodywork was created by Suzuki styling designers and engineers using numerous wind tunnel tests to achieve a slippery shape and compelling appearance. Narrower than ever before, the GSX-R1000 ABS's shape directly aids performance by improved handling and top speed on the racetrack.
- The dual SRAD intake ducts are positioned closer to the center of the fairing nose, where air pressure is highest. The intake ducts are also larger, thanks to the compact LED headlight.
- The reasonable sport riding position is created by a carefully crafted relationship between the clip-ons, footrests, and seat. Compared to the prior generation GSX-R, the top of the fuel tank is lowered 21 mm to make it easier for the rider to tuck in on a racetrack straightaway.
- The seat height is an appropriate 825 mm (32.48 in.) and contributes the good rider interface that aids in guiding the motorcycle on the road or racetrack.
- The passenger seat can be removed and exchanged with an optional, color-matched solo tail cowl.
- The shifter and rear brake pedal are adjustable in relationship to the footrests, and the hand controls are adjustable in relation to the grips. The front brake lever has a slot machined in the end to prevent wind pressure from applying the front brake.

ELECTRICAL FEATURES

- Controller Area Network wire harness (CAN Bus) allows for fast and precise communications between all of the GSX-R1000 ABS's electronic systems. With a CAN Bus system, riders will experience swift and trouble-free electronic system operation while the size and complexity of the wiring is simplified.
- The LCD multifunction instrument panel has an adjustable intensity, white-color backlight for great nighttime visibility and is flanked by LED indicators that include the turn signals, high beam, traction control, shift light, plus coolant temperature and oil pressure alerts.
- The LED headlight is lightweight, bright, and distinctive. This low-electric-draw light has a narrow, stacked shape to allow the SRAD ducts at the nose of the fair access to the high-pressure air created at higher speeds.
- The LED combination tail and brake light assembly has a very low electrical draw and the vertically stacked shape permits the tail section to be narrow for better air flow at the back of the motorcycle. License plate is also illuminated by an LED light.
- The turn signals are lightweight and use incandescent bulbs with amber lenses so the motorcycle's turn indication is highly visible to other traffic.
- The poly-function start/stop switch combines the engine stop and start functions. The switch is a fine complement to the Suzuki Easy Start system fitted to the GSX-R1000 ABS.
- The GSX-R1000 ABS now uses the same lightweight and compact battery as the GSX-R1000R.

ADDITIONAL FEATURES

- A variety of Genuine Suzuki Accessories are available, plus a large selection of GSX-R logo apparel.
- 12-month unlimited mileage, limited warranty.
 - Coverage can be increased via Suzuki Extended Protection
- For more details, please visit www.suzukicycles.com.

**The Traction Control System is not a substitute for the rider's throttle control. It cannot prevent loss of traction due to excessive speed when the rider enters a turn and/or applies the brakes. Neither can it prevent the front wheel from losing grip.*

**Depending on road surface conditions, such as wet, loose, or uneven roads, braking distance for an ABS-equipped vehicle may be longer than for a vehicle not equipped with ABS. ABS cannot prevent wheel skidding caused by braking while cornering. Please drive carefully and do not overly rely on ABS.*

2018

GSX-R1000 ABS



GSX-R1000 ABS SPECS

Engine:	4-stroke, liquid-cooled, 4-cylinder, DOHC
Displacement:	999.8cc
Bore x Stroke:	76.0 x 55.1 mm (2.992 x 2.169 in.)
Compression Ratio:	13.2:1
Fuel System:	Suzuki Fuel Injection with Ride-by-Wire throttle bodies
Starter:	Electric
Lubrication:	Wet sump
Transmission:	6-speed constant mesh
Clutch:	Wet, multi-plate type
Final Drive:	Chain, RK525GSH
Suspension, Front:	Inverted telescopic, coil spring, oil damped
Suspension, Rear:	Link type, single shock, coil spring, oil damped
Brakes, Front:	Brembo 4-piston, twin disc, ABS-equipped
Brakes, Rear:	Nissin, 1-piston, single disc, ABS-equipped

Tire, Front:	120/70ZR17M/C (58W), tubeless
Tire, Rear:	190/55ZR17M/C (73W), tubeless
Fuel Tank Capacity:	16.0 L (4.2 US gallons)
Ignition:	Electronic ignition (transistorized)
Headlight:	LED
Taillight:	LED
Overall Length:	2,075 mm (81.7 in.)
Overall Width:	705 mm (27.8 in.)
Overall Height:	1,145 mm (45.1 in.)
Wheelbase:	1,425 mm (56.1 in.)
Ground Clearance:	130 mm (5.11 in.)
Seat Height:	825 mm (32.5 in.)
Curb Weight:	201 kg (443.0 lbs.)
	202 kg (445.0 lbs.) California model

Suzuki Motor of America, Inc. makes every effort to present the most current specifications and product features at the time of publication. Because of our policy of continual improvement, changes may be made in equipment, availability, and specifications without notice or obligation. At Suzuki, we want every ride to be safe and enjoyable. So always wear a helmet, eye protection, and protective clothing. Never ride under the influence of alcohol or other drugs. Never engage in stunt riding. Avoid excessive speeds. Study your owner's manual and always inspect your Suzuki before riding. Take an MSF skills course; for the street course nearest you call 1-800-446-9227. Limited Warranty: The 2018 GSX-R1000 ABS limited warranty covers a period of 12 months. See your dealer for details. Ask your participating dealer about Genuine Suzuki Accessories and the Suzuki Retail Finance Plan and the Suzuki Extended Protection Plan. With the Suzuki Retail Finance Plan it's easy to afford and equip the machine that's perfect for you. VISIT SUZUKICYCLES.COM FOR MORE INFORMATION. Suzuki, the "S" logo, and Suzuki model and product names are Suzuki Trademarks or ®. © 2017 Suzuki Motor of America, Inc.