2018



- Fuel-injected 750cc, 4-cylinder engine powers a balanced sportbike experience

- Suzuki Drive Mode Selector (S-DMS) lets the rider adjust the power delivery

Twin-spar aluminum frame and Showa Big Piston Fork deliver extraordinary handling

- Twin Brembo monobloc, radially mounted front brakes deliver robust stopping power

- Race-ready, iconic GSX-R styling creates sharp looks and an aerodynamic shape





Metallic Triton Blue



Candy Daring Red / Glass Sparkle Black Metallic Oort Gray No. 3 / Glass Sparkle Black



2018



Three decades ago Suzuki revolutionized sport bikes with the introduction of the GSX-R750. Ever since then, the GSX-R750 has remained true to its original concept and championship-winning heritage. On the road or on the track, the GSX-R750 delivers a breathtaking combination of outstanding engine performance, crisp handling, compact size, and light weight. Its secret is an unequaled pairing of 750cc performance with the lightweight, compact chassis of a 600cc Supersport, complemented by technologically advanced suspension front and rear. Try a GSX-R750 and you'll quickly realize this motorcycle defines performance riding from the *center* of the sportbike class.

GSX-R750 FEATURES

ENGINE FEATURES

- Compact 750cc 4-cylinder engine with a race-proven over-square bore/stroke ratio produces remarkably strong high-RPM power delivery.
- The energy-efficient engine employs forged pistons, shot-peened connecting rods, chrome-nitride-coated upper compression and oil control rings, and pentagonal ventilation holes to reduce frictional and mechanical losses.
- Lightweight titanium-alloy valves are controlled by single-coil valve springs to reduce valve train mass, reducing mechanical losses at high RPM.
- Suzuki Dual Throttle Valve (SDTV) fuel injection uses eight fine-spray 8-hole injectors for improved fuel atomization, which contributes to more complete combustion.
- An Engine Control Module (ECM) provides state-of-the-art engine management and has enhanced settings to suit the intake and exhaust systems, resulting in better fuel economy and linear throttle response.
- Advanced, MotoGP-developed transistorized ignition control programming helps maintain more precise spark timing across the range of engine speed and temperature.
- Suzuki Drive Mode Selector (S-DMS) offers push-button selection of two racingdeveloped engine control maps to suit road or track conditions and personal tastes.
- 4-into-1 stainless-steel exhaust system with a titanium muffler is fitted with a Suzuki Exhaust Tuning (SET) valve that maximizes torque and improves throttle response, especially in the low- to mid-range RPM.
- The close-ratio 6-speed transmission features a taller first-gear ratio and shorter ratios for 2nd, 3rd, 4th, and 6th gear, making it easier for a racer to get a good start while improving straight-line acceleration and drive out of corners.
- Race-proven back-torque-limiting clutch contributes to smoother downshifting and corner entry.

CHASSIS FEATURES

- Lightweight and compact twin-spar aluminum-alloy frame is constructed of five cast sections to produce a balance of light weight and strength.
- The frame is mated with a cast aluminum swingarm and multi-piece rear sub-frame that's ready for racetrack use.
- Race-developed, lightweight Showa Big Piston Front Fork (BPF) delivers superb feedback and consistent performance.
- Single Showa rear shock features externally adjustable rebound and compression damping, along with adjustable ride height.

 Electronically controlled steering damper provides lighter steering at slower speeds and more damping force at racetrack and highway speeds.

7 -5101

- Front brakes with fully floating 310 mm discs are grasped by radial-mount, 4-piston Brembo monobloc calipers.
- 3-spoke cast-aluminum-alloy wheels are shod with lightweight, high-grip front and rear tires for sharp handling.
- 3-way adjustable footpegs, adjustable shift lever and short fuel tank help compose a comfortable riding position that permits the rider movement required for performance riding.
- Compact, lightweight instrument cluster with a built-in lap timer/stopwatch and programmable engine RPM indicators alert the rider to certain shift points.
- Trim, simple, and lightweight bodywork creates an exciting, aerodynamic style that truly works well at speed.
- Distinctive multi-reflector headlight with vertically stacked high- and low-beam halogen bulbs is centered between position lights on each side.
- · Bright, durable LED taillight with clear lens.
- The front turn signals are integrated into the rear-view mirrors while the rear tail section houses the rear signals.
- The lightweight instruments also include an analog tachometer and LCD readouts that show speed, odometer, dual trip meter, reserve trip meter, clock, coolant temperature/oil pressure indicator, S-DMS, and gear position indicators.
- Attention to rider comfort and confidence includes a carefully shaped seat with a high-grip cover.
- The wheel rims have pinstripes punctuated by "R" logos that highlight the bike's identity.

ADDITIONAL FEATURES

- Stylized Suzuki "S" 3-D emblems on the fuel tank and the fork upper bracket denote the quality, sophistication, and performance legacy of the brand.
- Optional single seat cowl can replace the passenger seat for an even more aggressive look or for use on solo rides or track days.
- A variety of Genuine Suzuki Accessories for GSX-R owners are available including a large selection of Suzuki logo apparel.
- · 12-month limited warranty.
- · For more details, please visit www.suzukicycles.com.

2018



GSX-R750 SPECS

Engine:	4-stroke, liquid-cooled, 4-cylinder, DOHC
Displacement:	750cc
Bore x Stroke:	70.0 x 48.7 mm (2.756 x 1.917 in.)
Compression Ratio:	12.5:1
Fuel System:	Suzuki Fuel Injection
Starter:	Electric
Lubrication:	Wet sump
Transmission:	6-speed constant mesh
Clutch:	Wet, multi-plate type
Final Drive:	Chain, RK525ROZ5Y, 116 links
Suspension, Front:	Inverted telescopic, coil spring, oil damped
Suspension, Rear:	Link type, single shock, coil spring, oil damped
Brakes, Front:	Brembo 4-piston, twin disc
Brakes, Rear:	Nissin, 1-piston, single disc

Tire, Front:	120/70ZR17M/C (58W), tubeless
Tire, Rear:	180/55ZR17M/C (73W), tubeless
Fuel Tank Capacity:	17.0 L (4.5 US gallons)
	16.0 L (4.2 US gallons) CA model
Ignition:	Electronic ignition (transistorized)
Spark Plugs:	NGK CR9EIA-9 or DENSO IU27D
Headlight:	12V 65W (H9 high-beam) & 12V 55W (H7 low-beam)
Taillight:	LED
Overall Length:	2,030 mm (79.9 in.)
Overall Width:	710 mm (28.0 in.)
Wheelbase:	1,135 mm (44.7 in.)
Ground Clearance:	130 mm (5.1 in.)
Seat Height:	810 mm (31.9 in.)
Curb Weight:	190 kg (419 lbs.)

Suzuki Motor of America, Inc. makes every effort to present the most current specifications and product features at the time of publication. Because of our policy of continual improvement, changes may be made in equipment, availability, and specifications without notice or obligation. At Suzuki, we want every ride to be safe and enjoyable. So always wear a helmet, eve protection, and protective clothing. Never ride under the influence of alcohol or other drugs. Never engage in stunt riding. Avoid excessive speeds. Study your owner's manual and always inspect your Suzuki before riding. Take an MSF skills course; for the street course nearest you call 1-800-446-9227. Limited Warranty: The 2018 GSX-R750 limited warranty covers a period of 12 months. See your dealer for details. Ask your participating dealer about Genuine Suzuki Accessories and the Suzuki Retail Finance Plan and the Suzuki Extended Protection Plan. With the Suzuki Retail Finance Plan it's easy to afford and equip the machine that's perfect for you. VISIT SUZUKICYCLES.COM FOR MORE INFORMATION. Suzuki, the "S" logo, and Suzuki model and product names are Suzuki Trademarks or ®. © 2017 Suzuki Motor of America, Inc.