



Motorcycle
2012 Model: DL650AL2
Date: October 2011

MSRP \$8,299



Metallic Fox Orange (YUK)

Key Features

1. Compact, slim styling featuring a vivid combination of expressive painted sections and functional black resin components accentuates the sporty profile.
2. The sporty, dynamic front fairing houses compact dual multi-reflector headlight delivering superb light distribution.
3. Stylish and functional front air intakes and side air outlets contribute to both looks and rider comfort.
4. 3-way height-adjustable windscreen, carefully shaped with extensive wind tunnel testing, efficiently reduces wind noise and rider fatigue.
5. Comfortable riding position composed with a well-shaped seat, slim 20-liter fuel tank and compactly tucked-in frame covers make the rider feel at one with the machine.

6. Functional seat, combining red-stitched leather-look sections and suede-look, slip-resistant surfaces, and topped with an embossed V-Strom logo.
7. The upswept muffler, topped with a silver cover and a buffed-finish end cap is gracing the rear end.
8. Lightweight resin luggage carrier comes with a slip-resistant rubber mat and is one piece with well-shaped, easy-to-grasp grab bars.
9. Instruments with an analog tachometer and brightness-adjustable LCD speedometer. LCD readouts include odometer, dual trip meter, gear position, coolant and ambient temperature, average fuel consumption, fuel gauge and clock.
10. Switching between LCD readings can be done with the left handlebar switch.
11. LED indicators include a road freeze warning indicator which, together with the ambient temperature display, helps riders' awareness of road conditions.
12. 645cm³ V-Twin engine features broad torque delivery, signature V-Twin power pulses and sporty quick-revving high rpm range power surges for a full-range riding enjoyment.
13. Efficient engine designs deliver high mileage and class-leading riding range.
14. Radiator with a more compact core, flanked by wind-directing plates shaped with holes* for enhancing cooling efficiency and allowing hot radiator air to flow out to the side air outlets and away from the rider's legs.
(*Patent application under process.)
15. The fuel injection system uses fine-atomization 10-hole fuel injectors for high combustion efficiency.
16. The 6-speed transmission is tailored for active sporty rides with tighter 1st through 5th gear ratios, while keeping highway cruises comfortable with a tall top gear.
17. A high-speed 32-bit ECU controls Suzuki Dual Throttle Valve (SDTV) system, contributing to enhanced low-to-mid rpm range torque, a linear throttle response and lower emissions.
18. Twin iridium spark plugs for each cylinder heighten the spark strength and combustion efficiency, contributing to increased power, a more linear throttle response, easier engine start-up and a more stable idle.

19. Suzuki-developed and patented Throttle-body Integrated Idle Speed Control (TI-ISC) contributes to easy cold starting, stable idle and lower emissions.
20. Lightweight and rigid twin-spar aluminum-alloy frame and swingarm contribute to smooth handling performance and well-poised running at high-speeds.
21. Spring-preload-adjustable 43mm-stanchion-tube front forks and link-type rear suspension with rebound stepless damping adjuster as well as a spring preload adjuster.
22. 19-inch front and 17-inch rear radial tires specifically designed for the V-Strom 650 ABS.
23. Front dual 310mm-disc brakes and rear 260mm-disc brake deliver smooth, controllable stopping power. Expansion-resistant high-pressure brake hose enhances the responsive brake feel.
24. Antilock Brake System (ABS)* unit features a lightweight, compact design. The ABS monitors wheel speed, and matches stopping power to available traction.
25. A wide selection of Suzuki Genuine Accessories, designed for a smooth, easy fit with the V-Strom 650 ABS, adds to both adventure tourer profile and function.

*Please note that ABS is a supplemental device for brake operation, not a device for shortening stopping distance. Always remember to reduce speed sufficiently before approaching curves and corners.



SPECIFICATIONS**MODEL: DL650AL2****DIMENSIONS AND CURB MASS**

Overall length.....	2290 mm (90.2 in)
Overall width.....	835 mm (32.9 in)
Overall height.....	1405 mm (55.3 in)
Wheelbase.....	1560 mm (61.4 in)
Ground clearance.....	175 mm (6.9 in)
Seat height.....	835 mm (32.9 in)
Curb mass.....	214 kg (472 lbs) 235 kg (519 lbs) - Adventure

ENGINE

Type.....	4-stroke, liquid-cooled, DOHC, 90° V-twin
Number of cylinders.....	2
Bore.....	81.0 mm (3.189 in)
Stroke.....	62.6 mm (2.465 in)
Displacement.....	645 cm ³ (39.4 cu. in)
Compression ratio.....	11.2 : 1
Fuel system.....	Fuel injection
Air cleaner.....	Non-woven fabric element
Starter system.....	Electric
Lubrication system.....	Wet sump
Idle speed.....	1300 ± 100 r/min

DRIVE TRAIN

Clutch.....	Wet multi-plate type
Transmission.....	6-speed constant mesh
Gearshift pattern1-down, 5-up
Primary reduction ratio.....	2.088 (71/34)
Gear ratios, Low.....	2.461 (32/13)
2nd.....	1.777 (32/18)
3rd.....	1.380 (29/21)
4th.....	1.125 (27/24)
5th.....	0.961 (25/26)
Top.....	0.851 (23/27)
Final reduction ratio.....	3.133 (47/15)
Drive chain.....	RK525SMOZ8, 118 links

CHASSIS

Front suspension.....	Telescopic, coil spring, oil damped
Rear suspension.....	Link type, coil spring, oil damped
Front fork stroke.....	150 mm (5.9 in)
Rear wheel travel.....	159 mm (6.3 in)
Caster.....	26°
Trail.....	110 mm (4.33 in)
Steering angle.....	40° (right & left)
Turning radius.....	2.7 m (8.9 ft)
Front brake.....	Disc brake, twin
Rear brake.....	Disc brake
Front tire.....	110/80R19 M/C 59H, tubeless
Rear tire.....	150/70R17 M/C 69H, tubeless

ELECTRICAL

Ignition type.....	Electronic ignition (Transistorized)
Ignition timing.....	8° B.T.D.C. at 1300 r/min
Spark plug.....	NGK CR8EIA-9 or DENSO IU24D
Battery.....	12V 36.0 kC (10 Ah)/10 HR
Generator.....	Three-phase A.C. generator
Main fuse.....	30A
Fuse.....	.15/.15/10/10/15/15 A
Headlight.....	12 V 60/55 W (H4) × 2
Position light.....	12 V 5 W × 2
Brake/Tail light.....	12 V 21/5 W × 2
Turn signal light.....	12 V 21 W
License plate light.....	12 V 5 W
Speedometer light.....	LED
Tachometer light.....	LED
Neutral indicator light.....	LED
High beam indicator light.....	LED
Turn signal indicator light.....	LED
Oil pressure/Coolant temperature/FI indicator light.....	LED
ABS indicator light.....	LED

CAPACITIES

Fuel tank.....	20.0 L (5.3/4.4 US/Imp gal)
Engine oil, oil change.....	2400 ml (2.5/2.1 US/Imp qt)
with filter change.....	2750 ml (2.9/2.4 US/Imp qt)
overhaul.....	3000 ml (3.2/2.6 US/Imp qt)
Coolant.....	1950 ml (2.0/1.7 US/Imp qt)

Model: DL650AL2 E-03, 21, 24, 28, 33
DL650AUEL2 E-21

Date: June 27, 2011

SERVICE DATA

VALVE + VALVE GUIDE

Unit: mm (in)

ITEM	STANDARD		LIMIT
Valve diam.	IN.	31.0 (1.22)	—
	EX.	25.5 (1.00)	—
Valve clearance (when cold)	IN.	0.10—0.20 (0.004—0.008)	—
	EX.	0.20—0.30 (0.008—0.012)	—
Valve guide to valve stem clearance	IN.	0.010—0.037 (0.0004—0.0015)	—
	EX.	0.030—0.057 (0.0012—0.0022)	—
Valve guide I.D.	IN. & EX.	4.500—4.512 (0.1772—0.1776)	—
Valve stem O.D.	IN.	4.475—4.490 (0.1762—0.1768)	—
	EX.	4.455—4.470 (0.1754—0.1760)	—
Valve stem deflection	IN. & EX.	—	0.35 (0.014)
Valve stem runout	IN. & EX.	—	0.05 (0.002)
Valve head thickness	IN. & EX.	—	0.5 (0.02)
Valve seat width	IN. & EX.	0.9—1.1 (0.035—0.043)	—
Valve head radial runout	IN. & EX.	—	0.03 (0.001)
Valve spring free length	IN. & EX.	—	37.1 (1.46)
Valve spring tension	IN. & EX.	127—147 N (12.7—12.7 kgf, 28.5—33.0 lbs) at length 33.4 mm (1.31 in)	—

CAMSHAFT + CYLINDER HEAD

Unit: mm (in)

ITEM	STANDARD		LIMIT
Cam height	IN.	35.48—35.55 (1.397—1.400)	35.18 (1.385)
	EX.	33.48—33.55 (1.318—1.321)	33.18 (1.306)
Camshaft journal oil clearance	IN. & EX.	0.027—0.069 (0.0011—0.0027)	0.150 (0.0059)
Camshaft journal holder I.D.	IN. & EX.	22.007—22.028 (0.8664—0.8672)	—
Camshaft journal O.D.	IN. & EX.	21.959—21.980 (0.8645—0.8654)	—
Camshaft runout	IN. & EX.	—	0.10 (0.004)
Cam chain pin (at arrow "3")	16th pin		—
Cylinder head distortion	—		0.05 (0.002)

CYLINDER + PISTON + PISTON RING

Unit: mm (in)

ITEM	STANDARD			LIMIT		
Compression pressure	1 300–1 700 kPa (13.0 – 17.0 kgf/cm ² , 185–242 psi)			1 100 kPa (11.0 kgf/cm ² , 156 psi)		
Compression pressure difference	—			200 kPa (2.0 kgf/cm ² , 28 psi)		
Piston to cylinder clearance	0.025–0.035 (0.0010–0.0014)			0.120 (0.0047)		
Cylinder bore	81.000–81.015 (3.1890–3.1896)			Nicks or scratches		
Piston diam.	80.970–80.985 (3.1878–3.1884) Measure at 20 mm (0.8 in) from the skirt end.			80.880 (3.1842)		
Cylinder distortion	—			0.05 (0.002)		
Piston ring free end gap	1st	—	Approx. 6.5 (0.26)	5.2 (0.20)		
	2nd	2T	Approx. 9.0 (0.35)	7.2 (0.28)		
Piston ring end gap	1st	—	0.06–0.18 (0.002–0.007)	0.50 (0.020)		
	2nd	2T	0.06–0.18 (0.002–0.007)	0.50 (0.020)		
Piston ring to groove clearance	1st	—		0.180 (0.0071)		
	2nd	—		0.150 (0.0059)		
Piston ring groove width	1st	0.83–0.85 (0.0327–0.0335) 1.30–1.32 (0.0512–0.0520)		—		
	2nd	1.01–1.03 (0.0398–0.0406)		—		
	Oil	2.01–2.03 (0.0791–0.0799)		—		
Piston ring thickness	1st	0.76–0.81 (0.0299–0.0319) 1.08–1.10 (0.0425–0.0433)		—		
	2nd	0.97–0.99 (0.0382–0.0390)		—		
Piston pin bore	20.002–20.008 (0.7875–0.7877)			20.030 (0.7886)		
Piston pin O.D.	19.992–20.000 (0.7871–0.7874)			19.980 (0.7866)		

CONROD + CRANKSHAFT

Unit: mm (in)

ITEM	STANDARD			LIMIT
Conrod small end I.D.	20.010–20.018 (0.7878–0.7881)			20.040 (0.790)
Conrod big end side clearance	0.170–0.320 (0.0067–0.0126)			0.5 (0.020)
Conrod big end width	20.95–21.00 (0.825–0.827)			—
Crank pin width	42.17–42.22 (1.660–1.662)			—
Conrod big end oil clearance	0.032–0.056 (0.0013–0.0022)			0.080 (0.0031)
Crank pin O.D.	37.976–38.000 (1.4951–1.4961)			—
Crankshaft journal O.D.	41.985–42.000 (1.6529–1.6535)			—
Crankshaft runout	—			0.05 (0.002)

OIL PUMP

ITEM	STANDARD			LIMIT
Oil pressure (at 60 °C, 140 °F)	200–600 kPa (2.0–6.0 kgf/cm ² , 28–85 psi) at 3 000 r/min			—

CLUTCH

Unit: mm (in)

ITEM	STANDARD		LIMIT
Clutch cable play	10–15 (0.4–0.6)		—
Clutch release screw	1 turn counterclockwise		—
Clutch drive plate thickness	No.1, 2	2.92–3.08 (0.115–0.121)	2.62 (0.103)
Clutch driven plate claw width	No.1, 2	13.7–13.8 (0.539–0.543)	12.9 (0.508)
Clutch driven plate distortion		—	0.10 (0.004)
Clutch spring free length		60.6 (2.39)	57.6 (2.27)

TRANSMISSION + DRIVE CHAIN

Unit: mm (in) Except ratio

ITEM	STANDARD		LIMIT
Primary reduction ratio	2.088 (71/34)		—
Final reduction ratio	3.133 (47/15)		—
Gear ratios	1st	2.461 (32/13)	—
	2nd	1.777 (32/18)	—
	3rd	1.380 (29/21)	—
	4th	1.125 (27/24)	—
	5th	0.961 (25/26)	—
	Top	0.851 (23/37)	—
Shift fork to groove clearance	No.1, 2, 3	0.1–0.3 (0.004–0.012)	0.5 (0.020)
Shift fork groove width	No.1, 2, 3	5.5–5.6 (0.217–0.220)	—
Shift fork thickness	No.1, 2, 3	5.3–5.4 (0.209–0.213)	—
Drive chain	Type	RK 525 SMOZ8	—
	Links	118 links	—
	20-pitch length	—	319.4 (12.57)
Drive chain slack (on side-stand)	20–30 (0.8–1.2)		—
Gearshift lever height	20–30 (0.8–1.2)		—

THERMOSTAT + RADIATOR + FAN + COOLANT

ITEM	STANDARD/SPECIFICATION		NOTE
Thermostat valve opening temperature	Approx. 82 °C (180 °F)		—
Thermostat valve lift	Over 8 mm (0.31 in) at 95 °C (203 °F)		—
Engine coolant temperature sensor resistance	20 °C (68 °F)	Approx. 2.45 kΩ	—
	50 °C (122 °F)	Approx. 0.811 kΩ	—
	80 °C (176 °F)	Approx. 0.318 kΩ	—
	110 °C (230 °F)	Approx. 0.142 kΩ	—
Radiator cap valve opening pressure	93–123 kPa (0.93–1.23 kgf/cm ² , 13.2–17.5 psi)		—
Cooling fan operating temperature	OFF→ON	Approx 105 °C (221 °F)	—
	ON→OFF	Approx 99 °C (210 °F)	—
Engine coolant type	Use an antifreeze/coolant compatible with aluminum radiator.		—
Engine coolant including reserve	Reverse tank side	Approx. 250 ml (0.3/0.2 US/Imp qt)	—
	Engine side	Approx. 1 700 ml (1.8/1.5 US/Imp qt)	—

INJECTOR + FUEL PUMP + FUEL PRESSURE REGULATOR

ITEM	SPECIFICATION	NOTE
Injector resistance	11.5 – 12.5 Ω at 20 °C (68 °F)	—
Fuel pump discharge amount	167 ml (5.6/5.9 US/Imp oz) or more /10 seconds, at 300 kPa (3.0 kgf/cm ² , 43 psi)	—
Fuel pressure regulator operating set pressure	Approx. 300 kPa (3.0 kgf/cm ² , 43 psi)	—

FI SENSORS + SECONDARY THROTTLE VALVE ACTUATOR

ITEM	SPECIFICATION		NOTE
CKP sensor resistance	130—240 Ω		
CKP sensor peak voltage	3.7 V or more		When cranking
IAP sensor input voltage	4.5—5.5 V		
IAP sensor output voltage	Approx. 2.5 V at idle speed		
TP sensor input voltage	4.5—5.5 V		
TP sensor output voltage	Closed	Approx. 1.1 V	
	Opened	Approx. 4.3 V	
ECT sensor input voltage	4.5—5.5 V		
ECT sensor resistance	Approx. 2.45 kΩ at 20 °C (68 °F)		
IAT sensor input voltage	4.5—5.5 V		
IAT sensor resistance	Approx. 2.6 kΩ at 20 °C (68 °F)		
TO sensor resistance	16.5—22.3 kΩ		
TO sensor voltage	Normal	0.4—1.4 V	
	Learning	3.7—4.4 V	When leaning 65 °
GP switch voltage	0.6 V or more		From 1st to Top
Injector voltage	Battery voltage		
Ignition coil primary peak voltage	150 V or more		When cranking
STP sensor input voltage	4.5—5.5 V		
STP sensor output voltage	Closed	Approx. 0.6 V	
	Opened	Approx. 4.5 V	
STV actuator resistance	Approx. 7 Ω		
HO2 sensor heater resistance	Approx. 8 Ω at 23 °C (73 °F)		
HO2 sensor output voltage	Idle speed	Approx. 0.45 V or less	
	6 000 r/min	0.6 V or more	
EXCVA system purge control solenoid valve resistance	Approx. 3.2Ω at 20 °C (68 °F)		E-33 only

THROTTLE BODY

ITEM	SPECIFICATION	
Bore size	39mm (1.53 in)	
I.D. No.	11J1 (E-33), 11J0 (Others)	
Idle r/min.	1 300 ± 100 r/min	
Fast idle r/min.	Approx. 2 000 r/min. (When cold engine)	
Throttle cable play	2.0—4.0 mm (0.08—0.16 in)	

ELECTRICAL

Unit: mm (in)

ITEM	STANDARD/SPECIFICATION		NOTE
Firing order	1·2		
Spark plug	Type	NGK: CR8EIA-9 DENSO: IU24D	
	Gap	0.8–0.9 (0.031–0.035)	
Spark performance	Over 8 mm (0.3 in) at 1 atm.		
CKP sensor resistance	130–240 Ω		
CKP sensor peak voltage	3.7 V or more		When cranking
Ignition coil resistance	Primary	1–3 Ω	Terminal – Terminal
	Secondary	25–40 kΩ	Plug cap – Plug cap
Ignition coil primary peak voltage	150 V or more		
Generator coil resistance	0.2–0.7 Ω		
Generator maximum output	Approx. 375 W at 5 000 r/min		
Generator no-load voltage (When engine is cold)	60 V (AC) or more at 5 000 r/min		
Regulated voltage	14.0–15.5 V at 5 000 r/min		
Starter motor brush length	Standard	12 (0.47)	
	Limit	6.5 (0.26)	
Starter relay resistance	3–6 Ω		
Battery	Type designation	FTX12-BS	
	Capacity	12 V 36.0 kC (10 Ah)/10 HR	
	Standard electrolyte S.G.	1.320 at 20 °C (68 °F)	
Fuse size	Headlight	HI	15 A
		LO	15 A
	Fuel		10 A
	Ignition		10 A
	Signal		10 A
	Fan		15 A
	Main		30 A
	ABS motor		25 A
	ABS valve		15 A

WATTAGE

Unit: W

ITEM	SPECIFICATION		
	E-03, 28, 33	E-21, 24	
Headlight	HI	60 × 2	←
	LO	55 × 2	←
Position/Parking light	5 × 2		←
Brake light/Taillight	21/5		←
Turn signal light	21 × 4		←
License plate light	5		←
Speedometer light	LCD		←
Tachometer light	LED		←
Turn signal indicator light	LED		←
High beam indicator light	LED		←
Neutral position indicator light	LED		←
Oil pressure Coolant /Engine temp indicator light	LED		←
FI indicator light	LED		←
Freeze indicator light	LED		←
ABS indicator light	LED		←
Immobilizer indicator light	—		LED

BRAKE + WHEEL

Unit: mm (in)

ITEM	STANDARD		LIMIT
Rear brake pedal height	23–33 (0.9–1.3)		—
Brake disc thickness	Front	4.8–5.2 (0.189–0.205)	4.5 (0.18)
	Rear	4.8–5.2 (0.189–0.205)	4.5 (0.18)
Brake disc runout	—		0.30 (0.012)
Master cylinder bore & piston diam.	Front	Approx. 14.0 (0.55)	—
	Rear	Approx. 14.0 (0.55)	—
Brake caliper cylinder bore & piston diam.	Front	Approx. 27.0 (1.06)	—
	Rear	Approx. 38.2 (1.50)	—
Brake fluid type	DOT 4		—
Wheel rim runout	Axial	—	2.0 (0.08)
	Radial	—	2.0 (0.08)
Wheel axle runout	Front	—	0.25 (0.010)
	Rear	—	0.25 (0.010)
Wheel rim size	Front	19 M/C×MT 2.50	—
	Rear	17 M/C×MT 4.00	—

TIRE

ITEM	STANDARD		LIMIT
Cold inflation tire pressure (Solo riding)	Front	225 kPa (2.25 kgf/cm ² , 33 psi)	—
	Rear	250 kPa (2.50 kgf/cm ² , 36 psi)	—
Cold inflation tire pressure (Dual riding)	Front	225 kPa (2.25 kgf/cm ² , 33 psi)	—
	Rear	280 kPa (2.90 kgf/cm ² , 41 psi)	—
Tire size	Front	110/80 R19 M/C 59H	—
	Rear	150/70 R17 M/C 69H	—
Tire type	Front	BRIDGESTONE: TW101 RADIAL J	—
	Rear	BRIDGESTONE: TW152 RADIAL F	—
Tire tread depth	Front	—	1.6 mm (0.06 in)
	Rear	—	2.0 mm (0.08 in)

SUSPENSION

Unit: mm (in)

ITEM	STANDARD	LIMIT
Front fork stroke	150 (5.9)	—
Front fork inner tube O.D.	43 (1.69)	—
Front fork spring free length	451.1 (17.8)	442 (17.4)
Front fork oil level (without spring, inner tube fully compressed)	139 (5.47)	—
Front fork oil type	SUZUKI FORK OIL SS-8 or an equivalent	—
Front fork oil capacity (each leg)	530 ml (17.9/18.7 US/Imp oz)	—
Front fork spring adjuster	2nd groove from top	
Rear shock absorber spring pre-set position	2nd position	—
Rear shock absorber damping force adjuster	2 turns from stiffest position	—
Rear wheel travel	159 (6.3)	—
Swingarm pivot shaft runout	—	0.3 (0.01)

FUEL + OIL

ITEM	SPECIFICATION		NOTE
Fuel type	Use only unleaded gasoline of at least 90 pump octane (R/2 + M/2). Gasoline containing MTBE (Methyl Tertiary Butyl Ether), less than 10% ethanol, or less than 5% methanol with appropriate cosolvents and corrosion inhibitor is permissible.		E-03, 28, 33
	Gasoline used should be graded 91 octane or higher. An unleaded gasoline is recommended.		E-21, 24
Fuel tank capacity	Including reserve	20.0 L (5.3/4.4 US/Imp gal)	
Engine oil type	SAE 10 W-40, API SF/SG or SH/SJ, or with JASO MA		
Engine oil capacity	Change	2 400 ml (2.5/2.1 US/Imp qt)	
	Filter change	2 750 ml (2.9/2.4 US/Imp qt)	
	Overhaul	3 000 ml (3.2/2.6 US/Imp qt)	

TIGHTENING TORQUE

ENGINE

ITEM		N·m	kgf·m	lbf·ft
Exhaust pipe bolt		23	2.3	16.5
Exhaust pipe connecting bolt		18	1.8	13.0
Muffler mounting bolt		23	2.3	16.5
Muffler mounting nut		23	2.3	16.5
Muffler cover bolt		10	1.0	7.0
Exhaust cover bolt		10	1.0	7.0
Speed sensor rotor bolt		28	2.8	20.5
Speed sensor mounting bolt		4.5	0.45	3.3
Engine sprocket nut		145	14.5	105.0
Engine mounting nut	Front upper	93	9.3	67.5
	Rear upper	55	5.5	40.0
Engine mounting bolt		55	5.5	40.0
Engine mounting pinch bolt		25	2.5	18.0
Engine mounting thrust adjuster		12	1.2	8.5
Engine mounting thrust adjuster lock-nut		45	4.5	32.5
Engine mounting bracket bolt		35	3.5	25.5
Cylinder head cover bolt		14	1.4	10.0
Intake pipe screw		8.5	0.85	6.0
Spark plug		11	1.1	8.0
Camshaft journal holder bolt		10	1.0	7.0
Oil pipe mounting bolt		10	1.0	7.0
Cam chain tensioner adjuster cap bolt		23	2.3	16.5
Cam chain tensioner adjuster mounting bolt		10	1.0	7.0
Cylinder head bolt	[M10]	25→42	2.5→4.2	18.0→30.5
	[M6]	10	1.0	7.0
Cylinder nut [M6]		10	1.0	7.0
Clutch sleeve hub nut		50	5.0	36.0
Clutch spring set bolt		10	1.0	7.0
Primary drive gear bolt		70	7.0	50.5
Starter clutch bolt		25	2.5	18.0
Generator rotor bolt		140	14.0	101.5
Generator stator set bolt		11	1.1	8.0
Generator cover bolt		10	1.0	7.0
Generator cover plug		11	1.1	8.0
Gearshift cam stopper bolt		10	1.0	7.0
Gearshift cam stopper plate bolt		13	1.3	9.5
Gearshift arm stopper		19	1.9	13.5
Gearshift lever bolt		40	4.0	29.0
Clutch release arm bolt		9	0.9	6.5
Gear position switch mounting bolt		6.5	0.65	4.7
Throttle cable lock-nut		4.5	0.45	3.3
Engine sprocket cover bolt		5.5	0.55	4.0
Oil pressure switch		14	1.4	10.0
Oil pressure switch lead wire bolt		1.5	0.15	1.0
Crankcase bolt	[M6]	11	1.1	8.0
	[M8]	26	2.6	19.0

ITEM		N·m	kgf-m	lbf-ft
Oil gallery plug	(Cylinder head) [M6]	10	1.0	7.0
	[M6]	10	1.0	7.0
	[M8]	18	1.8	13.0
	[M12]	21	2.1	15.0
	[M16]	35	3.5	25.5
Oil drain plug		21	2.1	15.0
Piston cooling oil jet bolt		10	1.0	7.0
Conrod cap bolt		21 N·m (2.1 kgf-m, 15.0 lbf-ft) → turn clockwise 90°		
Oil cooler union bolt		70	7.0	50.5
Oil filter		20	2.0	14.5
Oil pipe stopper screw		8	0.8	5.7
Oil plate bolt		10	1.0	7.0
Oil pressure regulator		27	2.7	19.5
Oil pump mounting bolt		10	1.0	7.0
Starter motor mounting bolt		6	0.6	4.5
Starter motor housing bolt		10	1.0	7.0
Starter motor lead wire mounting bolt		5	0.5	3.5

FI SYSTEM AND INTAKE AIR SYSTEM

ITEM		N·m	kgf-m	lbf-ft
CKP sensor mounting bolt		6.5	0.65	4.7
Fuel delivery pipe mounting screw		3.5	0.35	2.5
Fuel pump mounting bolt		10	1.0	7.0
TP sensor mounting screw		3.5	0.35	2.5
STP sensor mounting screw		3.5	0.35	2.5
ECT sensor		18	1.8	13.0
IAT sensor screw		1.5	0.15	1.0
GP switch mounting bolt		6.5	0.65	4.7
HO2 sensor		25	2.5	18.0
EVAP system purge control solenoid valve mounting nut (E-33 only)		7	0.7	5.0
EVAP system purge control valve Bracket screw		5	0.5	3.5

COOLING SYSTEM

ITEM		N·m	kgf-m	lbf-ft
Water pump cover screw		4.5	0.45	3.3
Engine coolant drain plug		13	1.3	9.5
Water hose clamp bolt		1.5	0.15	1.0
Cooling fan assembly mounting bolt		5	0.5	3.5

CHASSIS

ITEM	N·m	kgf-m	lbf-ft
Steering stem head nut	90	9.0	65.0
Steering stem nut	45 N·m (4.5 kgf-m, 32.5 lbf-ft) → turn counterclockwise 1/4–1/2		
Steering stem lock-nut	80	8.0	58.0
Front fork upper clamp bolt	23	2.3	16.5
Front fork lower clamp bolt	23	2.3	16.5
Front fork cap bolt	23	2.3	16.5
Front fork cylinder bolt	20	2.0	14.5
Front axle	65	6.5	47.0
Front axle pinch bolt	23	2.3	16.5
Front footrest bracket bolt	26	2.6	19.0
Handlebar holder bolt	23	2.3	16.5
Front brake master cylinder mounting bolt	10	1.0	7.0
Front brake caliper mounting bolt	39	3.9	28.0
Brake hose union bolt	23	2.3	16.5
Brake disc bolt (Front & Rear)	23	2.3	16.5
Air bleeder valve (front brake caliper)	7.5	0.75	5.5
Air bleeder valve (rear brake caliper)	6	0.6	4.5
Rear brake caliper mounting bolt	23	2.3	16.5
Rear brake caliper sliding pin	27	2.7	19.5
Rear brake pad mounting pin	17	1.7	12.5
Pad pin plug	2.5	0.25	1.8
Rear brake master cylinder mounting bolt	10	1.0	7.0
Rear brake master cylinder rod lock-nut	18	1.8	13.0
Wheel speed sensor rotor bolt	6.5	0.65	4.7
Rear axle nut	100	10.0	72.5
Rear sprocket nut	60	6.0	43.5
Side-stand bolt	100	10.0	72.5
Side-stand pivot bolt	50	5.0	36.0
Side-stand pivot nut	40	4.0	29.0
Side-stand switch mounting bolt	14	1.4	10.0
Swingarm pivot nut	100	10.0	72.5
Swingarm pivot lock-nut	90	9.0	65.0
Swingarm pivot shaft	15	1.5	11.0
Rear shock absorber mounting upper nut	50	5.0	36.0
Rear shock absorber mounting lower nut	50	5.0	36.0
Cushion lever mounting nut	78	7.8	56.5
Cushion rod mounting nut	78	7.8	56.5
Brake lever pivot bolt	6	0.6	4.5
Brake lever pivot bolt lock-nut	6	0.6	4.5
Clutch lever pivot bolt	6.5	0.65	4.7
Clutch lever pivot bolt lock-nut	6.5	0.65	4.7

ITEM	N·m	kgf·m	lbf·ft
Combination meter bolt	4.5	0.45	3.3
Combination meter screw	1.5	0.15	1.0
Rear combination light mounting screw	1.8	0.18	1.5
Turn signal light mounting nut (Front)	1.3	0.13	1.0
Turn signal light mounting nut (Rear)	2.3	0.23	1.7
License plate mounting bolt	5	0.5	3.5
Reflex reflector	2	0.2	1.5
Reflex reflector bolt	4.5	0.45	3.3
Reflex reflector nut	1.8	0.18	1.5
Sport carrier bolt	29	2.9	21.0
Bank sensor bolt	18	1.8	13.0
Brake pipe flare nut	16	1.6	11.5