

Features & Specifications

2018 GSX-R600



GSX-R600L8

YSF: Metallic Triton Blue

Key Features

- Fuel-injected 599cc, 4-cylinder, engine delivers a rush of power from idle to redline.
- Suzuki Drive Mode Selector (S-DMS) lets the rider tailor the power delivery.
- Twin-spar aluminum frame and SHOWA big piston front fork delivers exceptional handling.
- Twin Brembo Monobloc, radially mounted, front brakes deliver strong stopping power.
- Race-ready, iconic GSX-R styling delivers sharp looks and a slippery shape.

Overview

The Suzuki GSX-R600 is a class-leading sport bike worthy of its race-winning GSX-R heritage. Whether you're carving through your favorite canyon or dominating the racetrack, it offers unparalleled performance. A compact, powerful 4-cylinder engine demonstrates the advanced race-proven technology of the GSX-R line when you hit the throttle and push it to redline, while supremely refined suspension systems front and rear help provide precise, responsive handling. Wrapped in aerodynamic and light-weight bodywork that's lifted from the race track, the GSX-R600 can not only win races, it can win envy.

Engine Features

- Compact 599cc 4-cylinder engine with a race-proven over-square bore/stroke ratio that produces remarkably strong high RPM power delivery.
- The energy efficient engine employs forged pistons, shot-peened connecting rods, chrome-nitride-coated upper compression and oil control rings, and pentagonal ventilation holes to reduce frictional and mechanical losses.
- Camshafts with aggressive valve-lift profiles were developed using proven MotoGP racing engine technology – the first time this method has been applied to a production Suzuki.
- Lightweight titanium-alloy valves are controlled by single coil valve springs to reduce valve train mass, reducing mechanical losses at high RPM.
- Lightweight and durable forged pistons were designed using the same Finite Element Method (FEM) and fatigue analysis technology used for MotoGP racing engines.
- Suzuki Dual Throttle Valve (SDTV) fuel injection uses eight, fine-spray 8-hole injectors for improved fuel atomization, which contributes to more complete combustion.

- An Engine Control Module (ECM) provides state-of-the-art engine management and has enhanced settings to suit the intake and exhaust systems, resulting in better fuel economy and linear throttle response.
- Advanced, MotoGP-developed transistorized ignition control programming helps maintain more precise spark timing across the range of engine speed and temperature range.
- Suzuki Drive Mode Selector (S-DMS) offers push-button selection of two racing-developed engine control maps to suit road or track conditions, and personal tastes.
- 4-into-1 stainless-steel exhaust system with a titanium muffler is fitted with a Suzuki Exhaust Tuning (SET) valve that maximizes torque and improves throttle response, especially in the low-to-mid RPM range.
- The close-ratio six-speed transmission features a taller first-gear ratio and shorter ratios for 2nd, 3rd, 4th and 6th gear, making it easier for a racer to get a good start while improving straight-line acceleration and drive out of corners.
- Race-proven back-torque-limiting clutch contributes to smoother downshifting and corner entry.



GSX-R600L8

QEB: Metallic Oort Gray No.3

Chassis Features

- Lightweight and compact twin-spar aluminum-alloy frame is constructed of five cast sections to produce a balance of light weight and strength.
- The frame is mated with a cast aluminum swingarm and multi-piece rear sub-frame that's ready for race-track adaptation.
- Race-developed, lightweight SHOWA Big Piston front Forks (BPF) deliver superb feedback and consistent performance.
- Single SHOWA rear shock features externally adjustable rebound and compression damping, along with adjustable ride height.
- Electronically controlled steering damper provides lighter steering at slower speeds and more damping force at racetrack and highway speeds.
- Front brakes with fully floating 310mm discs are grasped by radial-mount, four-piston BREMBO monobloc calipers.

- Three-spoke cast-aluminum-alloy wheels are shod with lightweight, high-grip front and rear tires for sharp handling.
- Three-way adjustable footpegs, adjustable shift lever and short fuel tank help compose a comfortable riding position that permits the positions required for performance riding.
- Compact, lightweight instrument cluster with a built-in lap timer/stopwatch and programmable engine RPM indicators to alert the rider to certain shift points.
- Trim, simple and lightweight bodywork creates an exciting, aerodynamic style that truly works well at speed.
- Distinctive multi-reflector headlight with vertically stacked high and low-beam halogen bulbs is centered between position lights on each side.
- Bright, durable LED taillight, with clear lens.
- The front turn signal are integrated into the rear-view mirrors while the rear tail section houses the rear signals.
- The lightweight instruments also include an analog tachometer and LCD readouts that show speed, odometer, dual trip meter, reserve trip meter, clock, coolant temperature/oil pressure indicator, S-DMS and gear position indicators.
- Attention to rider comfort and confidence includes a carefully shaped seat with a high-grip cover.
- The wheel rims have pin stripes punctuated by “R” logos that highlight the bike’s identity.



GSX-R600L8

BNE: Metallic Mystic Silver / Pearl Glacier White

Additional Features

- Stylized Suzuki “S” 3-D emblems on the fuel tank and the fork upper bracket denotes the quality, sophistication and performance legacy of the brand.
- Optional single seat cowl can replace the passenger seat for an even more aggressive look or for use on solo rides, or track days.
- A variety of Genuine Suzuki Accessories for GSX-R owners are available including a large selection of Suzuki logo apparel.
- 12-month limited warranty
- For more details, please visit www.suzukicycles.com.

Specifications GSX-R600L8

E-03: USA, E-33: California

DIMENSIONS AND CURB MASS

Overall length	2030 mm (79.9 in)
Overall width	710 mm (28.0 in)
Overall height	1135 mm (44.7 in)
Wheelbase	1385 mm (54.5 in)
Ground clearance	130 mm (5.1 in)
Seat height	810 mm (31.9 in)
Curb mass	187 kg (412 lbs)

ENGINE

Type	4-stroke, liquid-cooled, DOHC
Number of cylinders	4
Bore	67.0 mm (2.638 in)
Stroke	42.5 mm (1.673 in)
Displacement	599 cm ³ (36.5 cu. in)
Compression ratio	12.9 : 1
Fuel system	Fuel injection
Air cleaner	Paper element
Starter system	Electric
Lubrication system	Wet sump
Idle speed	1300 ± 100 r/min

DRIVE TRAIN

Clutch	Wet multi-plate type
Transmission	6-speed constant mesh
Gearshift pattern	1-down, 5-up
Primary reduction ratio	1.974 (77/39)
Gear ratios, Low	2.687 (43/16)
2nd	2.105 (40/19)
3rd	1.761 (37/21)
4th	1.521 (35/23)
5th	1.347 (31/23)
Top	1.230 (32/26)
Final reduction ratio	2.687 (43/16)
Drive chain	RK525SMOZ8, 114 links

CHASSIS

Front suspension	Inverted telescopic, coil spring, oil damped
Rear suspension	Link type, coil spring, oil damped
Front fork stroke	120 mm (4.7 in)
Rear wheel travel	130 mm (5.1 in)
Caster	23° 45'
Trail	97 mm (3.82 in)
Steering angle	27° (right & left)
Turning radius	3.4 m (11.2 ft)
Front brake	Disc brake, twin
Rear brake	Disc brake
Front tire	120/70ZR17M/C (58W), tubeless
Rear tire	180/55ZR17M/C (73W), tubeless

Specifications GSX-R600L8

E-03: USA, E-33: California

ELECTRICAL

Ignition type.....	Electronic ignition (Transistorized)
Ignition timing.....	1° B.T.D.C. at 1300 r/min
Spark plug.....	NGK CR9EIA-9 or DENSO IU27D
Battery.....	12V 28.8 kC (8 Ah)/10 HR
Generator.....	Three-phase A.C. generator
Main fuse.....	30A
Fuse.....	10/10/10/10/10/15A
Headlight.....	12V 65W (H9) + 12V 55W (H7)
Position light.....	12V 5W × 2
Brake/Tail light.....	LED
Turn signal light.....	12V 21W
License plate light.....	12V 5W
Combination meter light.....	LED
Neutral indicator light.....	LED
High beam indicator light.....	LED
Turn signal indicator light.....	LED
Fuel level indicator light.....	LED
Oil pressure/Coolant temperature indicator light.....	LED
FI/SD indicator light.....	LED
Engine RPM indicator light.....	LED

CAPACITIES

Fuel tank.....	16.0 L (4.2/3.5 US/Imp gal) ...E-33
	17.0 L (4.5/3.7 US/Imp gal) ...E-03
Engine oil, oil change.....	2200 ml (2.3/1.9 US/Imp qt)
with filter change.....	2500 ml (2.6/2.2 US/Imp qt)
overhaul.....	2900 ml (3.1/2.6 US/Imp qt)
Coolant.....	2.7 L (2.9/2.4 US/Imp qt)

Service Data GSX-R600L8

E-03: USA, E-33: California

Valve + Guide

Unit: mm (in)

Item		Standard	Limit
Valve diam.	IN.	27.2 (1.07)	—
	EX.	22.0 (0.87)	—
Valve clearance (when cold)	IN.	0.08 – 0.18 (0.003 – 0.007)	—
	EX.	0.18 – 0.28 (0.007 – 0.011)	—
Valve guide to valve stem clearance	IN.	0.010 – 0.037 (0.0004 – 0.0015)	—
	EX.	0.030 – 0.057 (0.0012 – 0.0022)	—
Valve guide I.D.	IN. & EX.	4.500 – 4.512 (0.1772 – 0.1776)	—
Valve stem O.D.	IN.	4.475 – 4.490 (0.1762 – 0.1768)	—
	EX.	4.455 – 4.470 (0.1754 – 0.1760)	—
Valve stem deflection	IN. & EX.	—	0.25 (0.010)
Valve stem runout	IN. & EX.	—	0.05 (0.002)
Valve seat width	IN. & EX.	0.9 – 1.1 (0.035 – 0.043)	—
Valve head radial runout	IN. & EX.	—	0.03 (0.001)
Valve spring free length	IN. & EX.	—	39.4 (1.55)
Valve spring tension	IN. & EX.	215 – 247 N (21.9 – 25.2 kgf, 48.3 – 55.5 lbs) at length 33.55 mm (1.321 in)	—

Camshaft + Cylinder Head

Unit: mm (in)

Item		Standard	Limit
Cam height	IN. & EX.	35.78 – 35.83 (1.409 – 1.411)	35.48 (1.397)
Camshaft journal oil clearance	IN. & EX.	0.032 – 0.066 (0.0013 – 0.0026)	0.150 (0.0059)
Camshaft journal holder I.D.	IN. & EX.	24.012 – 24.025 (0.9454 – 0.9459)	—
Camshaft journal O.D.	IN. & EX.	23.959 – 23.980 (0.9433 – 0.9441)	—
Camshaft runout		—	0.10 (0.004)
Cam chain pin (at arrow “3”)		12th pin	—
Cylinder head distortion		—	0.20 (0.008)

Cylinder + Piston + Piston Ring

Unit: mm (in)

Item	Standard			Limit
Compression pressure	1 300 – 1 700 kPa (13 – 17 kgf/cm ² , 185 – 242 psi)			1 000 kPa (10 kgf/cm ² , 142 psi)
Compression pressure difference	—			200 kPa (2 kgf/cm ² , 28 psi)
Piston-to-cylinder clearance	0.030 – 0.040 (0.0012 – 0.0016)			0.120 (0.0047)
Cylinder bore	67.000 – 67.015 (2.6378 – 2.6384)			No nicks or Scratches
Piston diam.	66.965 – 66.980 (2.6364 – 2.6370) Measure 13.5 mm (0.53 in) from the skirt end.			66.880 (2.6331)
Cylinder distortion	—			0.20 (0.008)
Piston ring free end gap	1st	IT	Approx. 5.5 (0.22)	4.4 (0.17)
	2nd	2T	Approx. 7.5 (0.30)	6.0 (0.24)
Piston ring end gap	1st	IT	0.06 – 0.21 (0.002 – 0.008)	0.50 (0.020)
	2nd	2T		
Piston ring-to-groove clearance	1st	—		0.180 (0.0071)
	2nd	—		0.150 (0.0059)
Piston ring groove width	1st	1.01 – 1.03 (0.0398 – 0.0406)		—
	2nd	0.81 – 0.83 (0.0319 – 0.0327)		—
	Oil	1.51 – 1.53 (0.0594 – 0.0602)		—
Piston ring thickness	1st	0.97 – 0.99 (0.0382 – 0.0390)		—
	2nd	0.77 – 0.79 (0.0303 – 0.0311)		—
Piston pin bore	14.002 – 14.008 (0.5513 – 0.5515)			14.030 (0.5524)
Piston pin O.D.	13.995 – 14.000 (0.5510 – 0.5512)			13.980 (0.5504)

Conrod + Crankshaft

Unit: mm (in)

Item	Standard			Limit
Conrod small end I.D.	14.010 – 14.018 (0.5516 – 0.5519)			14.040 (0.5528)
Conrod big end side clearance	0.10 – 0.20 (0.004 – 0.008)			0.30 (0.012)
Conrod big end width	19.95 – 20.00 (0.7854 – 0.7874)			—
Crank pin width	20.10 – 20.15 (0.7913 – 0.7933)			—
Conrod big end oil clearance	0.032 – 0.056 (0.0013 – 0.0022)			0.080 (0.0031)
Crank pin O.D.	30.976 – 31.000 (1.2195 – 1.2205)			—
Crankshaft journal oil clearance	0.010 – 0.028 (0.0004 – 0.0011)			0.080 (0.0031)
Crankshaft journal O.D.	29.982 – 30.000 (1.18039 – 1.18110)			—
Crankshaft thrust bearing thickness	Right side	2.425 – 2.450 (0.0955 – 0.0965)		—
	Left side	2.350 – 2.500 (0.0925 – 0.0984)		—
Crankshaft thrust clearance	0.055 – 0.110 (0.0022 – 0.0043)			—
Crankshaft runout	—			0.05 (0.002)

Oil Pump

Item	Standard	Limit
Oil pressure (at 60 °C, 140 °F)	100 – 400 kPa (1.0 – 4.0 kgf/cm ² , 14 – 57 psi) at 3 000 r/min	—

Clutch

Unit: mm (in)

Item	Standard	Limit
Clutch drive plate thickness	No. 1 & 2 2.72 – 2.88 (0.107 – 0.113)	2.42 (0.095)
Clutch drive plate claw width	No. 1 & 2 13.85 – 13.96 (0.545 – 0.550)	13.05 (0.514)
Clutch driven plate distortion	—	0.10 (0.004)
Clutch spring free length	66.47 (2.617)	63.2 (2.49)
Clutch lifter pin height	0.2 – 0.4 (0.008 – 0.016)	—
Wave spring washer height	—	4.30 (0.169)
Clutch lever play	10 – 15 (0.4 – 0.6)	—
Clutch release screw	1 turn back	—

Drive Train

Unit: mm (in) Except ratio

Item	Standard	Limit
Primary reduction ratio	1.974 (77/39)	—
Final reduction ratio	2.687 (43/16)	—
Gear ratios	Low	2.687 (43/16)
	2nd	2.105 (40/19)
	3rd	1.761 (37/21)
	4th	1.521 (35/23)
	5th	1.347 (31/23)
	Top	1.230 (32/26)
Gearshift fork to groove clearance	0.1 – 0.3 (0.004 – 0.012)	0.5 (0.02)
Gearshift fork groove width	5.0 – 5.1 (0.197 – 0.201)	—
Gearshift fork thickness	4.8 – 4.9 (0.189 – 0.193)	—
Drive chain	Type	RK 525SMOZ8
	Links	114 links
	20-pitch length	—
Drive chain slack (on side-stand)	20 – 30 (0.8 – 1.2)	—
Gearshift lever height	65 – 75 (2.6 – 3.0)	—

Thermostat + Radiator + Fan + Coolant

Item	Standard/Specification	Note
Thermostat valve opening temperature	Approx. 82 °C (180 °F)	—
Thermostat valve lift	Over 8 mm (0.31 in) and at 95 °C (203 °F)	—
ECT sensor resistance	20 °C (68 °F)	Approx. 2.45 kΩ
	50 °C (122 °F)	Approx. 0.811 kΩ
	80 °C (176 °F)	Approx. 0.318 kΩ
	110 °C (230 °F)	Approx. 0.142 kΩ
Radiator cap valve opening pressure	108 – 137 kPa (1.1 – 1.4 kgf/cm ² , 15.4 – 19.5 psi)	—
Cooling fan operating temperature	OFF → ON	Approx. 105 °C (221 °F)
	ON → OFF	Approx. 100 °C (212 °F)
	OFF → ON	Approx. 100 °C (212 °F)
	ON → OFF	Approx. 95 °C (203 °F)
Engine coolant type	Use an anti-freeze/coolant compatible with aluminum radiator.	—
Engine coolant including reserve	Reserve tank side	Approx. 250 ml (0.3/0.2 US/Imp qt)
	Engine side	Approx. 2 400 ml (2.5/2.1 US/Imp qt)

Injector + Fuel Pump + Fuel Pressure Regulator

Item	Specification	Note
Injector resistance	Approx. 12 Ω at 20 °C (68 °F)	Primary and secondary
Fuel pump discharge amount	167 ml (5.6/5.9 US/Imp oz) and more/10 sec.	
Fuel pressure regulator operating set pressure	Approx. 300 kPa (3.0 kgf/cm ² , 43 psi)	

FI Sensors

Item	Standard/Specification	Note
CKP sensor resistance	Approx. 168 Ω at 20 °C (68 °F)	
CKP sensor peak voltage	0.28 V and more	When cranking
IAP sensor input voltage	4.5 – 5.5 V	
IAP sensor output voltage	Approx. 2.7 V at idle speed	
TP sensor input voltage	4.5 – 5.5 V	
TP sensor output voltage	Closed	1.02 – 1.22 V
	Opened	4.34 – 4.54 V
ECT sensor input voltage	4.5 – 5.5 V	
ECT sensor output voltage	0.15 – 4.85 V	
ECT sensor resistance	Approx. 2.45 k Ω at 20 °C (68 °F)	
IAT sensor input voltage	4.5 – 5.5 V	
IAT sensor output voltage	0.15 – 4.85 V	
IAT sensor resistance	Approx. 2.58 k Ω at 20 °C (68 °F)	
AP sensor input voltage	4.5 – 5.5 V	
AP sensor output voltage	Approx. 3.6 V at 100 kPa (760 mmHg)	
TO sensor resistance	Approx. 19.4 k Ω at 20 °C (68 °F)	
TO sensor voltage	Normal	0.4 – 1.4 V
	Leaning	3.7 – 4.4 V
GP switch voltage	0.6 V and more	When leaning 65° From 1st to Top
Injector voltage	Battery voltage	Primary and secondary
Ignition coil primary peak voltage	80 V and more	When cranking
HO2 sensor output voltage	0.4 V and less at idle speed	
	0.6 V and more at 5 000 r/min	
HO2 sensor heater resistance	6.7 – 9.5 Ω at 23 °C (73 °F)	
PAIR control solenoid valve resistance	20 – 24 Ω at 20 – 30 °C (68 – 86 °F)	
STP sensor input voltage	4.5 – 5.5 V	
STP sensor output voltage	Closed	0.52 – 0.72 V
	Opened	4.12 – 4.32 V
STVA resistance	Approx. 6.5 Ω	
EXCVA position sensor input voltage	4.5 – 5.5 V	
EXCVA position sensor output voltage	Closed	0.45 – 1.4 V
	Opened	3.6 – 4.55 V
EXCVA position sensor resistance	Approx. 3.1 k Ω	At adjustment position
EVAP system purge control solenoid valve resistance	Approx. 32 Ω at 20 °C (68 °F)	If equipped
ISC valve resistance	Approx. 20 Ω at 20 °C (68 °F)	
Steering damper solenoid valve resistance	Approx. 12.5 Ω at 20 °C (68 °F)	
Steering damper solenoid valve voltage	Approx. 10 V	When battery fully charged

Throttle Body

Item	Specification
Bore size	40 mm (1.57 in)
I.D. No.	14J1 (For E-33), 14J0 (For E-03)
Idle r/min	1 300 ± 100 r/min
Throttle cable play	2.0 – 4.0 mm (0.08 – 0.16 in)

Electrical

Unit: mm (in)

Item	Specification	Note	
Firing order	1 · 2 · 4 · 3		
Spark plug	Type	NGK: CR9EIA-9 DENSO: IU27D	
	Gap	0.8 – 0.9 (0.031 – 0.035)	
Spark performance	Over 8 (0.3) at 1 atm.		
CKP sensor resistance	Approx. 168 Ω at 20 °C (68 °F)		
CKP sensor peak voltage	0.28 V and more	When cranking	
Ignition coil resistance	Primary	1.1 – 1.5 Ω at 20 °C (68 °F)	
	Secondary	6.4 – 9.6 kΩ at 20 °C (68 °F)	
Ignition coil primary peak voltage	80 V and more	When cranking	
Generator coil resistance	0.2 – 1.0 Ω		
Generator maximum output	Approx. 400 W at 5 000 r/min		
Generator no-load voltage (When engine is cold)	65 V (AC) and more at 5 000 r/min		
Regulated voltage	14.0 – 15.5 V at 5 000 r/min		
Starter motor brush length	Standard	12.0 (0.47)	
	Limit	6.5 (0.26)	
Starter relay resistance	3 – 6 Ω		
Battery	Type designation	FTX9-BS	
	Capacity	12 V 28.8 kC (8 Ah)/10 HR	
	Standard electrolyte S.G.	1.320 at 20 °C (68 °F)	
Fuse size	Headlight	HI	10 A
		LO	10 A
	Ignition	10 A	
	Signal	10 A	
	Fuel	10 A	
	Fan	15 A	
	Main	30 A	

Wattage

Unit: W

Item		Specification
Headlight	HI	65
	LO	55
Position light		5 x 2
Brake/Tail light		LED
Turn signal light		21 x 4
License plate light		5
Combination meter light		LED
Turn signal indicator light		LED
High beam indicator light		LED
Neutral position indicator light		LED
Oil pressure indicator light/Engine coolant temp. indicator light		LED
FI indicator light/Sd indicator light		LED
Fuel level indicator light		LED
Engine RPM indicator light		LED

Brake + Wheel

Unit: mm (in)

Item	Standard		Limit	
Rear brake pedal height	65 – 75 (2.6 – 3.0)		—	
Brake disc thickness	Front	4.8 – 5.2 (0.19 – 0.20)	4.5 (0.18)	
	Rear			
Brake disc runout	—		0.30 (0.012)	
Master cylinder bore & piston diam.	Front	Approx. 17.5 (0.69)	—	
	Rear	Approx. 14.0 (0.55)	—	
Brake caliper cylinder bore & piston diam.	Front	Leading	Approx. 32.0 (1.26)	
		Trailing		
	Rear	Approx. 30.2 (1.19)		—
		DOT 4		—
Wheel rim runout	Axial	—	2.0 (0.08)	
	Radial			
Wheel rim size	Front	17 M/C x MT 3.50	—	
	Rear	17 M/C x MT 5.50	—	
Wheel axle runout	Front	—	0.25 (0.010)	
	Rear			

Tire

Item	Standard		Limit
Cold inflation tire pressure (Solo riding)	Front	250 kPa (2.50 kgf/cm ² , 36 psi)	—
	Rear	290 kPa (2.90 kgf/cm ² , 42 psi)	—
Cold inflation tire pressure (Dual riding)	Front	250 kPa (2.50 kgf/cm ² , 36 psi)	—
	Rear	290 kPa (2.90 kgf/cm ² , 42 psi)	—
Tire size	Front	120/70 ZR17M/C (58 W)	—
	Rear	180/55 ZR17M/C (73 W)	—
Tire type	Front	BRIDGESTONE BATT LAX BT016F AA	—
	Rear	BRIDGESTONE BATT LAX BT016R AA	—
Tire tread depth (Recommended depth)	Front	—	1.6 mm (0.06 in)
	Rear	—	2.0 mm (0.08 in)

Suspension

Unit: mm (in)

Item	Standard		Limit
Front fork stroke	120 (4.7)		—
Front fork spring free length	238.3 (9.38)		233 (9.2)
Front fork oil level	90 (3.5)		—
	80 (3.1) 10 min. after adjustment		—
Front fork oil type	FORK OIL SS-47 or an equivalent fork oil		—
Front fork oil capacity (Each leg)	487 ml (16.5/17.1 US/Imp oz)		—
Front fork inner tube O.D	41 (1.6)		—
Front fork spring adjuster	6-1/4 turns in from full soft position		—
Front fork damping force adjuster	Rebound	4 turns out from full hard position	—
	Compression	4-1/2 turns out from full hard position	—
Rear shock absorber spring pre-set length	180 (7.2)		—
Rear shock absorber damping force adjuster	Rebound	2-3/4 turns out from full hard position	—
	Compression	Lo: 1-3/4 turns out from full hard position Hi: 2-3/4 turns out from full hard position	—
Rear wheel travel	130 (5.1)		—
Swingarm pivot shaft runout	—		0.3 (0.01)

Fuel + Oil

Item	Specification		Note	
Fuel type	Use only unleaded gasoline of at least 90 pump octane (R/2 + M/2). Gasoline containing MTBE (Methyl Tertiary Butyl Ether), less than 10% ethanol, or less than 5% methanol with appropriate cosolvents and corrosion inhibitor is permissible.			
Fuel tank capacity	Including reserve	16 L (4.2/3.5 US/Imp gal)	E-33	
		17 L (4.5/3.7 US/Imp gal)	E-03	
	Fuel level indicator light lighting	blink	Approx. 3.9 L (1.0/0.9 US/Imp gal)	
		lighting	Approx. 1.5 L (0.4/0.3 US/Imp gal)	
Engine oil type	SAE 10W-40, API SF/SG or SH/SJ with JASO MA			
Engine oil capacity	Change	2 200 ml (2.3/1.9 US/Imp qt)		
	Filter change	2 500 ml (2.6/2.2 US/Imp qt)		
	Overhaul	2 900 ml (3.1/2.6 US/Imp qt)		



Tightening Torque List

Engine

Item		N·m	kgf·m	lbf·ft	
Exhaust pipe bolt		23	2.3	16.5	
Exhaust chamber support bolt		23	2.3	16.5	
Exhaust chamber support bracket bolt		26	2.6	19.0	
Muffler connecting bolt		23	2.3	16.5	
Muffler cover bolt		11	1.1	8.0	
Muffler support bolt		26	2.6	19.0	
Speed sensor rotor bolt		28	2.8	20.0	
Speed sensor bolt		4.5	0.45	3.0	
Engine sprocket nut		115	11.5	83.0	
Engine mounting bolt (Cylinder)		55	5.5	39.8	
Engine mounting nut (Crankcase)		75	7.5	54.0	
Engine mounting thrust adjuster		23	2.3	16.5	
Engine mounting thrust adjuster lock-nut		45	4.5	32.5	
Engine mounting pinch bolt		23	2.3	16.5	
Cylinder head cover bolt		14	1.4	10.0	
Spark plug		11	1.1	8.0	
Cam chain guide No. 1 bolt		23	2.3	16.5	
Camshaft journal holder bolt		10	1.0	7.0	
Cam chain tension adjuster service cap		23	2.3	16.5	
Cam chain tension adjuster mounting bolt		10	1.0	7.0	
Cam chain tensioner bolt		23	2.3	16.5	
CKP sensor rotor/cam chain drive sprocket bolt		54	5.4	39.0	
Cylinder head bolt	[M10]	31 N·m (3.1 kgf·m, 22.5 lbf·ft) then turn in 1/6 (60°) turn			
	[M6]	10	1.0	7.0	
Clutch sleeve hub nut		95	9.5	68.5	
Clutch spring set bolt		10	1.0	7.0	
Clutch release adjuster cap		11	1.1	8.0	
Clutch push rod adjusting screw lock-nut		5.5	0.55	4.0	
Clutch lifter pin lock-nut		23	2.3	16.5	
Clutch cable lock-nut		4.5	0.45	3.0	
Crankshaft hole plug		11	1.1	8.0	
Starter clutch bolt		15	1.5	11.0	
Generator rotor bolt		120	12.0	87.0	
Generator stator set bolt		11	1.1	8.0	
Generator lead wire clamp bolt		5.5	0.55	4.0	
Oil pressure switch		14	1.4	10.0	
Oil pressure switch lead wire screw		1.5	0.15	1.0	
Oil filter		20	2.0	14.5	
Crankshaft journal bolt	[M9]	18 N·m (1.8 kgf·m, 13.0 lbf·ft) then turn in 50°			
Crankcase bolt	[M6]	Initial	6	0.6	4.5
		Final	11	1.1	8.0
	[M8]	Initial	15	1.5	11.0
		Final	26	2.6	19.0
Oil gallery plug		7	0.7	5.0	
Oil gallery plug	[M6]	10	1.0	7.0	
	[M12]	15	1.5	11.0	
	[M16]	35	3.5	25.5	
Oil drain plug		23	2.3	16.5	
Oil gallery jet		27	2.7	19.5	
Piston cooling oil jet bolt		10	1.0	7.0	
Conrod cap bolt		15 N·m (1.5 kgf·m, 11.0 lbf·ft) then turn in 1/4 (90°) turn			
Oil cooler mounting bolt		10	1.0	7.0	



Item		N·m	kgf·m	lbf·ft
Driveshaft bearing cover bolt	Initial	6	0.6	4.5
	Final	12	1.2	8.5
Driveshaft bearing case bolt (LH and RH)		12	1.2	8.5
Driveshaft retainer bolt		12	1.2	8.5
Gearshift arm stopper		19	1.9	13.5
Gearshift cam stopper bolt		10	1.0	7.0
Gearshift cam plate bolt		13	1.3	9.5
Gearshift cam bearing retainer screw		10	1.0	7.0
Gearshift shaft end screw		8.5	0.85	6.1
Gearshift lever shaft		40	4.0	29.0
Gearshift lever bracket bolt		28	2.8	20.0
Push rod oil seal retainer bolt		10	1.0	7.0
Starter motor mounting bolt		10	1.0	7.0
Starter motor lead wire mounting nut		6	0.6	4.5
Starter motor housing bolt		5	0.5	3.5
Starter motor brush holder nut		11	1.1	8.0
PAIR solenoid valve bracket mounting bolt		11	1.1	8.0
Throttle cable nut		4.5	0.45	3.0

FI System + Intake Air System

Item		N·m	kgf·m	lbf·ft
CMP sensor bolt		10	1.0	7.0
TP sensor mounting screw		3.5	0.35	2.5
STP sensor mounting screw		3.5	0.35	2.5
ISC valve mounting screw		2	0.2	1.5
CKP sensor mounting screw		5.5	0.55	4.0
CKP sensor clamp screw		5.5	0.55	4.0
HO2 sensor		25	2.5	18.0
Fuel delivery pipe mounting screw		3.5	0.35	2.5
Fuel pump mounting bolt		10	1.0	7.0
EXCVA pulley mounting bolt		5	0.5	3.5
EXCV cable bracket mounting nut		11	1.1	8.0
IAP sensor mounting screw		3.5	0.35	2.5
IAT sensor mounting bolt		1.5	0.15	1.0
GP switch mounting bolt		6.5	0.65	4.5
Intake pipe bolt		10	1.0	7.0
Intake pipe clamp screw		1.5	0.15	1.0
Air cleaner box cover screw		1.5	0.15	1.0
Air cleaner holder bolt		10	1.0	7.0
Funnel bolt		4.3	0.43	3.0
EVAP pipe mounting bolt (if equipped)		10	1.0	7.0
EVAP system purge control solenoid valve mounting nut (if equipped)		10	1.0	7.0
EVAP system purge control solenoid valve bracket bolt (if equipped)		10	1.0	7.0



Chassis

Item	N·m	kgf-m	lbf-ft
Steering stem head nut	90	9.0	65.0
Steering stem lock-nut	80	8.0	58.0
Steering damper bolt	23	2.3	16.5
Steering damper nut	23	2.3	16.5
Front fork upper clamp bolt	23	2.3	16.5
Front fork lower clamp bolt	23	2.3	16.5
Front fork cap bolt	35	3.5	25.5
Front fork piston rod nut	28	2.8	20.0
Front fork rod guide case	90	9.0	65.0
Front axle nut	100	10.0	72.5
Front axle pinch bolt	23	2.3	16.5
Handlebar clamp bolt	23	2.3	16.5
Handlebar balancer screw	5.5	0.55	4.0
Master cylinder holder bolt (Upper and Lower)	10	1.0	7.0
Front brake caliper mounting bolt	39	3.9	28.0
Brake hose union bolt	23	2.3	16.5
Air bleeder valve (Front caliper)	7.5	0.75	5.5
Air bleeder valve (Rear caliper)	6.0	0.6	4.5
Air bleeder valve (Front master cylinder)	6.0	0.6	4.5
Brake disc bolt (Front)	18	1.8	13.0
Brake disc bolt (Rear)	35	3.5	25.5
Rear brake pad mounting pin	18	1.8	13.0
Rear brake pad mounting pin plug	2.5	0.25	2.0
Rear brake caliper sliding pin A	27	2.7	19.5
Rear brake caliper sliding pin B	13	1.3	9.5
Rear brake master cylinder mounting bolt	10	1.0	7.0
Rear brake master cylinder rod lock-nut	18	1.8	13.0
Brake lever pivot bolt	1	0.1	0.7
Brake lever pivot bolt lock-nut	6	0.6	4.5
Clutch lever pivot nut	6.5	0.65	4.7
Clutch lever holder bolt	10	1.0	7.0
Swingarm pivot shaft	15	1.5	11.0
Swingarm pivot nut	100	10.0	72.5
Swingarm pivot lock-nut	90	9.0	65.0
Cushion lever mounting nut	98	9.8	71.0
Cushion rod mounting nut	98	9.8	71.0
Rear shock absorber bracket nut	100	10.0	72.5
Rear shock absorber mounting nut (Upper and Lower)	50	5.0	36.0
Spring adjuster lock-nut	35	3.5	25.5
Rear axle nut	100	10.0	72.5
Rear sprocket nut	60	6.0	43.0
Rear combination light mounting bolt	5	0.5	3.5
License plate light mounting nut	5	0.5	3.5
Side-stand nut	40	4.0	29.0
Side-stand bolt	50	5.0	36.0

Item	N·m	kgf-m	lbf-ft
Side-stand bracket mounting bolt	50	5.0	36.0
Bank sensor bolt	18	1.8	13.0
Footrest bracket bolt	23	2.3	16.5
Footrest guard screw (Left side)	4.5	0.45	3.0
Footrest holder bolt	35	3.5	25.5
Pillion footrest bracket bolt	23	2.3	16.5
Seat rail mounting bolt	50	5.0	36.0
Cowling brace mounting nut	38	3.8	27.5
Rear fender (Lower) mounting bolt	10	1.0	7.0
Rear view mirror mounting nut	10	1.0	7.0
Front reflector bolt (if equipped)	10	1.0	7.0
Front reflex reflector (if equipped)	1.8	0.18	1.3
Rear reflex reflector nut (if equipped)	1.8	0.18	1.3
Under cowling mounting screw (right side)	6.5	0.65	4.7

Cooling System

Item	N·m	kgf-m	lbf-ft
Impeller securing bolt	8	0.8	6.0
Water pump case screw	5.5	0.55	4.0
Water pump air bleeder bolt	13	1.3	9.5
Water pump mounting bolt	10	1.0	7.0
ECT sensor	18	1.8	13.0
Radiator reservoir tank bolt	6	0.6	4.5
Water hose clamp screw	1.5	0.15	1.0

Suzuki Motor of America, Inc. makes every effort to present the most current specifications and product features at the time of publication. Because of our policy of continual improvement, changes may be made in equipment, availability and specifications without notice or obligation. At Suzuki, we want every ride to be safe and enjoyable. Always wear a helmet, eye protection and protective clothing. Never ride under the influence of alcohol or other drugs. Study your owner's manual and always inspect your Suzuki before riding. Always supervise young riders. Take an MSF skills course. For the street course nearest you call 1-800-446-9227. Preserve your future riding opportunities by showing respect for the environment, local laws and the rights of others when you ride. Limited Warranty: The 2018 GSX-R600 limited warranty covers a period of 12 months. See your dealer for details. Ask your participating dealer about Genuine Suzuki Accessories and the Suzuki Retail Finance Plan and the Suzuki Extended Protection Plan. With the Suzuki Retail Finance Plan it's easy to afford and equip the machine that's perfect for you. VISIT SUZUKICYCLES.COM FOR MORE INFORMATION. Suzuki Motor of America, Inc., 3251 East Imperial Highway, P.O. Box 1100, Brea, CA 92822-1100, Suzuki, the "S" logo, and Suzuki model names are Suzuki trademarks or ®. ©Suzuki Motor of America, Inc. 2017

