

Features & Specifications

2019 DR200S



DR200SL9

30H: Solid Special White No. 2

Key Features

- Commute, travel, or trail ride – the DR200S is ready to do it all.
- Reliable 199cc thumper delivers excellent fuel economy of 88 MPG.
- Comfortably low seat height of 33.3 inches and weighs just 278 pounds.
- Rider-friendly push-button electric starter.
- Champion-approved RM-Z styling.

Overview

The 2019 Suzuki DR200S is the affordable motorcycle that can tackle a dirt trail or be a street commuter that gets 88MPG with its reliable 199cc engine complete with push-button electric-starting, telescopic front forks, a 3.3 gallon tank, and abundant torque. This makes the DR200S is the intelligent choice for trail enthusiasts and commuters alike. With sharp, competition-like styling, Solid Special White bodywork with new, distinctive graphics, and a reasonable 33.3 inch seat height, this 278 pound cycle delivers the agile maneuverability and fun Suzuki is known for.

**Suzuki's fuel economy estimates are based on EPA exhaust emission measurement tests conducted by Suzuki and are intended for comparison purposes only. Your actual mileage may vary depending on how you ride and maintain your vehicles, road and driving conditions, tires pressure, engine break-in, accessories, cargo, rider and passenger weight, and other factors.*

Engine Features

- Ultra-reliable 199cc, air-cooled, SOHC single-cylinder engine provides just the right amount of torque and horsepower to power your ride.
- Suzuki Composite Electrochemical Material (SCEM) coated aluminum cylinder is used for durability, weight reduction and superior heat transfer.
- Push-button electric start fires up the bike consistently, powered by a small and reliable battery.
- Digitally controlled CDI ignition system to match ignition timing throughout the engine rpm range.
- Five-speed transmission with gear ratios suitable for a wide variety of riding conditions.
- Cable-operated, quick-action rack-and-pinion clutch design ensures light and positive operation.
- Engine power routes to the rear wheel via a low-maintenance, long-life sealed chain.

Chassis Features

- Influenced by the high-performance style of the RM-Z series, the ergonomic design makes the DR200S a better fit to a wider range of riders for the dirt and the pavement.
- Compact and sturdy high-tensile strength steel pipe frame.
- Telescopic front forks and single shock absorber rear suspension with adjustable spring preload have sufficient wheel travels of both front and rear 8.1 inches.
- Front disc and rear drum brakes deliver reliable stopping power.
- Large front and thick rear tires with special tread patterns are designed for smooth riding for on and off the pavement.
- Backward-folding rearview mirrors, gearshift and brake pedals help reduce damage from obstacle impact.



Chassis Features

- Electric start system provides convenient operation and features a lightweight starter motor and a compact, maintenance-free battery.
- A 60/55 watt H4 halogen headlight can help extend your riding session.
- The taillight and turn signals match the sleek style of the seat and bodywork.
- The on-road legal lighting is complemented with rubber-mounted turn signals and horn.

Additional Features

- 12-month limited warranty. Longer coverage periods with other benefits are available through Suzuki Extended Protection (SEP).
- Genuine Suzuki Accessories for DR200S owners are available including a selection of Suzuki logo apparel.
- For more details, please visit www.suzukicycles.com.

Suzuki Motor of America, Inc. makes every effort to present the most current specifications and product features at the time of publication. Because of our policy of continual improvement, changes may be made in equipment, availability and specifications without notice or obligation. At Suzuki, we want every ride to be safe and enjoyable. Always wear a helmet, eye protection and protective clothing. Never ride under the influence of alcohol or other drugs. Study your owner's manual and always inspect your Suzuki before riding. Always supervise young riders. Take an MSF skills course. For the street course nearest you call 1-800-446-9227. Preserve your future riding opportunities by showing respect for the environment, local laws and the rights of others when you ride. Limited Warranty: The 2019 Suzuki DR200S's limited warranty covers a period of 12 months. See your dealer for details. Ask your participating dealer about Genuine Suzuki Accessories and the Suzuki Retail Finance Plan and the Suzuki Extended Protection Plan. With the Suzuki Retail Finance Plan it's easy to afford and equip the machine that's perfect for you. VISIT SUZUKICYCLES.COM FOR MORE INFORMATION. Suzuki Motor of America, Inc., 3251 East Imperial Highway, P.O. Box 1100, Brea, CA 92822-1100, Suzuki, the "S" logo, and Suzuki model names are Suzuki trademarks or ®. ©2018 Suzuki Motor of America, Inc.

Specifications DR200SL9

E-03: USA, E-33: California

DIMENSIONS AND CURB MASS

Overall length.....	2 155 mm (84.8 in)
Overall width.....	805 mm (31.7 in)
Overall height.....	1 140 mm (44.9 in)
Wheelbase.....	1 405 mm (55.3 in)
Ground clearance.....	255 mm (10.0 in)
Seat height.....	845 mm (33.3 in)
Curb mass.....	126 kg (278 lbs)

ENGINE

Type.....	Four-stroke, air-cooled, OHC
Number of cylinders.....	1
Bore.....	66.0 mm (2.60 in)
Stroke.....	58.2 mm (2.29 in)
Displacement.....	199 cm ³ (12.1 cu. in)
Compression ratio.....	9.4 : 1
Carburetor.....	MIKUNI BST31SS, single
Air cleaner.....	Polyurethane foam element
Starter system.....	Electric
Lubrication system.....	Wet sump
Idle speed.....	1 500 ± 100 r/min

DRIVE TRAIN

Clutch.....	Wet multi-plate type
Transmission.....	5 speed constant mesh
Gearshift pattern.....	1-down, 4-up
Primary reduction.....	3.157 (60/19)
Final reduction.....	3.000 (45/15)
Gear ratios, Low.....	3.000 (33/11)
2nd.....	1.933 (29/15)
3rd.....	1.437 (23/16)
4th.....	1.095 (23/21)
Top.....	0.913 (21/23)
Drive chain.....	DID 520V, 112 links

CHASSIS

Front suspension.....	Telescopic, coil spring, oil damped
Rear suspension.....	Link type, coil spring, oil damped
Front fork stroke.....	205 mm (8.1 in)
Rear wheel travel.....	205 mm (8.1 in)
Caster.....	29°
Trail.....	112 mm (4.4 in)
Steering angle.....	43° (right & left)
Turning radius.....	2.3 m (7.5 ft)
Front brake.....	Disc brake
Rear brake.....	Drum brake
Front tire.....	70/100-21M/C 44P, tube type
Rear tire.....	100/90-18M/C 56P, tube type

ELECTRICAL

Ignition type.....	Electronic ignition (CDI)
Ignition timing.....	7° B.T.D.C. at 1 500 r/min
Spark plug.....	NGK DR8EA or DENSO X24ESR-U
Battery.....	12 V 21.6 kC (6 Ah)/10 HR
Generator.....	Three-phase A.C. generator
Fuse.....	20 A
Headlight.....	12 V 60/55 W
Brake light/Taillight.....	12 V 21/5 W
Turn signal light.....	12 V 21 W
Speedometer light.....	12 V 1.7 W
Neutral indicator light.....	12 V 2 W
Turn signal indicator light.....	12 V 2 W
High beam indicator light.....	12 V 2 W

CAPACITIES

Fuel tank, including reserve.....	12.5 L (3.3/2.7 US/Imp gal)
reserve.....	12.0 L (3.2/2.6 US/Imp gal)California
change.....	2.5 L (0.7/0.5 US/Imp gal)
Engine oil.....	850 ml (0.9/0.7 US/Imp qt)
with filter change.....	950 ml (1.0/0.8 US/Imp qt)
overhaul.....	1 100 ml (1.2/1.0 US/Imp qt)

Service Data DR200SL9

E-03: USA, E-33: California

VALVE + VALVE GUIDE

Unit: mm (in)

ITEM		STANDARD	LIMIT
Valve diam.	IN.	33.0 (1.30)	—
	EX.	28.0 (1.10)	—
Valve clearance (when cold)	IN.	0.05 – 0.10 (0.002 – 0.004)	—
	EX.	0.08 – 0.13 (0.003 – 0.005)	—
Valve guide to valve stem clearance	IN.	0.010 – 0.037 (0.0004 – 0.0015)	—
	EX.	0.030 – 0.057 (0.0012 – 0.0022)	—
Valve guide I.D.	IN. & EX.	5.500 – 5.512 (0.2165 – 0.2170)	—
Valve stem O.D.	IN.	5.475 – 5.490 (0.2146 – 0.2161)	—
	EX.	5.455 – 5.470 (0.2148 – 0.2154)	—
Valve stem deflection	IN. & EX.	—	0.35 (0.014)
Valve stem runout	IN. & EX.	—	0.05 (0.002)
Valve head thickness	IN. & EX.	—	0.5 (0.02)
Valve stem end length	IN. & EX.	—	2.6 (0.1)
Valve seat width	IN. & EX.	0.9 – 1.1 (0.04 – 0.05)	—
Valve head radial runout	IN. & EX.	—	0.03 (0.001)
Valve spring free length (IN. & EX.)	INNER	—	35.1 (1.38)
	OUTER	—	40.6 (1.60)
Valve spring tension (IN. & EX.)	INNER	70 – 90 N (7.1 – 9.2 kgf, 15.7 – 20.3 lbf) at length 32.5 mm (1.28 in)	—
	OUTER	170 – 209 N (17.3 – 21.3 kgf, 38.1 – 47.0 lbf) at length 36.0 mm (1.42 in)	—

CAMSHAFT + CYLINDER HEAD

Unit: mm (in)

ITEM	STANDARD		LIMIT
Cam height	IN.	34.174 – 34.218 (1.3454 – 1.3472)	33.870 (1.3335)
	EX.	33.804 – 33.848 (1.3309 – 1.3326)	33.500 (1.3189)
Camshaft journal oil clearance	IN. & EX.	0.032 – 0.066 (0.0013 – 0.0026)	0.150 (0.0059)
Camshaft journal holder I.D.	IN. & EX.	22.012 – 22.025 (0.8666 – 0.8671)	—
Camshaft journal O.D.	IN. & EX.	21.959 – 21.980 (0.8645 – 0.8654)	—
Camshaft runout	IN. & EX.	—	0.10 (0.004)
Rocker arm I.D.	IN. & EX.	12.000 – 12.018 (0.4724 – 0.4731)	—
Rocker arm shaft O.D.	IN. & EX.	11.977 – 11.995 (0.4715 – 0.4722)	—
Cylinder head distortion	—		0.05 (0.002)
Cylinder head cover distortion	—		0.05 (0.002)

CYLINDER + PISTON + PISTON RING

Unit: mm (in)

ITEM	STANDARD		LIMIT
Compression pressure	1 400 kPa (14 kgf/cm ² , 199 psi)		980 kPa (9.8 kgf/cm ² , 139 psi)
Piston to cylinder clearance	0.020 – 0.030 (0.0008 – 0.0012)		0.120 (0.0047)
Cylinder bore	65.980 – 65.995 (2.5976 – 2.5982)		66.115 (2.6030)
Piston diam.	65.955 – 65.970 (2.5966 – 2.5972) Measure at 15 mm (0.59 in) from the skirt end.		65.835 (2.5919)
Cylinder distortion	—		0.05 (0.002)
Piston ring free end gap	1st	R	Approx. 8.7 (0.34)
	2nd	R	Approx. 8.1 (0.32)
Piston ring end gap	1st	0.10 – 0.25 (0.004 – 0.010)	
	2nd	0.10 – 0.25 (0.004 – 0.010)	
Piston ring to groove clearance	1st	—	
	2nd	—	

ITEM	STANDARD		LIMIT
Piston ring groove width	1st	1.01 – 1.04 (0.040 – 0.041)	
	2nd	1.21 – 1.23 (0.047 – 0.048)	
	Oil	2.01 – 2.03 (0.079 – 0.080)	
Piston ring thickness	1st	0.970 – 0.990 (0.038 – 0.039)	—
	2nd	1.170 – 1.190 (0.046 – 0.047)	—
Piston pin bore	16.002 – 16.008 (0.6300 – 0.6302)		16.030 (0.6311)
Piston pin O.D.	15.996 – 16.000 (0.6298 – 0.6299)		15.980 (0.6291)

CONROD + CRANKSHAFT

Unit: mm (in)

ITEM	STANDARD	LIMIT
Conrod small end I.D.	16.006 – 16.016 (0.6302 – 0.6306)	16.040 (0.6315)
Conrod deflection	—	3.0 (0.12)
Conrod big end side clearance	0.10 – 0.45 (0.004 – 0.018)	1.00 (0.039)
Conrod big end width	17.95 – 18.00 (0.707 – 0.709)	—
Crank web to web width	53.0 ± 0.1 (2.09 ± 0.004)	—
Crankshaft runout	—	0.08 (0.003)

OIL PUMP

ITEM	STANDARD	LIMIT
Oil pump reduction ratio	2.000 (30/15)	—
Oil pressure (at 60 °C, 140 °F)	Above 15 kPa (0.15 kgf/cm ² , 2.1 psi) Below 35 kPa (0.35 kgf/cm ² , 4.9 psi) at 3 000 r/min	—

CLUTCH

Unit: mm (in)

ITEM	STANDARD	LIMIT
Clutch lever play	10 – 15 (0.4 – 0.6)	—
Clutch release screw	1/4 turn back	—
Clutch plate thickness	2.9 – 3.1 (0.114 – 0.122)	2.6 (0.10)
Driven plate distortion	—	0.10 (0.004)
Clutch spring free length	—	31.0 (1.22)

TRANSMISSION + DRIVE CHAIN

Unit: mm (in) Except ratio

ITEM		STANDARD	LIMIT
Primary reduction ratio		3.157 (60/19)	—
Final reduction ratio		3.000 (45/15)	—
Gear ratios	Low	3.000 (33/11)	—
	2nd	1.933 (29/15)	—
	3rd	1.437 (23/16)	—
	4th	1.095 (23/21)	—
	Top	0.913 (21/23)	—
Shift fork to groove clearance		0.10 – 0.30 (0.004 – 0.012)	—
Shift fork groove width	No.1, 2, 3	5.0 – 5.1 (0.20 – 0.21)	—
Shift fork thickness	No.1, 2, 3	4.8 – 4.9 (0.18 – 0.19)	—
Drive chain	Type	D.I.D. 520V5	—
	Links	112 links	—
	20-pitch length	—	319.4 (12.57)
Drive chain slack		25 – 40 (1.0 – 1.6)	—

CARBURETOR

ITEM	SPECIFICATION	
	E-03	E-33 (For California)
Carburetor type	MIKUNI BST31SS	←
Bore size	31 mm	←
I.D. No.	42AC	42AE
Idle r/min	1 500 ± 100 r/min	←
Float height	13.0 ± 1.0 mm (0.51 ± 0.04 in)	←
Main jet (M.J.)	#125	←
Jet needle (J.N.)	5D77	←
Needle jet (N.J.)	P-5M	←
Throttle valve (Th.V.)	#125	←
Pilot jet (P.J.)	#35	←
Starter jet (G.S.)	#25	←
Pilot screw (P.S.)	PRE-SET	←
Throttle cable play	2 – 4 mm (0.08 – 0.16 in)	←

ELECTRICAL

Unit: mm (in)

ITEM		SPECIFICATION		NOTE
Spark plug		Type	DENSO: X24ESR-U NGK: DR8EA	
		Gap	0.6 – 0.7 (0.024 – 0.028)	
Spark performance		Over 8 mm (0.3) at 1 atm.		
Signal coil resistance		148 – 222 Ω		B/R – G
Signal coil peak voltage		4.5 V or more		⊕ B/R – ⊖ G
Ignition coil resistance		Primary	0.14 – 0.18 Ω	Terminal – Ground (core)
		Secondary	15.0 – 17.4 k Ω	Plug cap – Terminal
Ignition coil primary peak voltage		200 – 240 V		⊕ Ground (core) – ⊖ W
Generator coil resistance		0.54 – 0.66 Ω		
Generator no-load voltage (When engine is cold)		55 – 85 V (AC) at 5 000 r/min		
Generator Max. output		150 W at 5 000 r/min		
Regulated voltage		13.0 – 16.0 V at 5 000 r/min		
Starter relay resistance		2 – 6 Ω		
Battery	Type designation	YTX7L-BS		
	Capacity	12 V 21.6 kC (6 Ah)/10 HR		
Fuse size		20 A		

WATTAGE

Unit: W

ITEM		SPECIFICATION
Headlight	HI	60
	LO	55
Brake light/Taillight		21/5
Turn signal light		21
Speedometer light		1.7
Turn signal indicator light		2
High beam indicator light		2
Neutral indicator light		2

BRAKE + WHEEL

Unit: mm (in)

ITEM	STANDARD		LIMIT
Brake lever play	0.1 – 0.3 (0.004 – 0.010)		—
Rear brake pedal free travel	20 – 30 (0.8 – 1.2)		—
Rear brake pedal height	2.5 (0.10)		—
Brake drum I.D.	Rear	—	130.7 (5.15)
Brake lining thickness	Rear	—	1.5 (0.06)
Brake disc thickness	Front	3.5 ± 0.2 (0.138 ± 0.008)	3.0 (0.12)
Brake disc runout	Front	—	0.30 (0.012)
Master cylinder bore	Front	12.700 – 12.743 (0.5000 – 0.5017)	—
Master cylinder piston diam.	Front	12.657 – 12.684 (0.4983 – 0.4994)	—
Brake caliper cylinder bore	Front	33.960 – 34.010 (1.3370 – 1.3390)	—
Brake caliper piston diam.	Front	33.878 – 33.928 (1.3338 – 1.3357)	—
Wheel rim runout	Axial	—	2.0 (0.08)
	Radial	—	2.0 (0.08)
Wheel axle runout	Front	—	0.25 (0.010)
	Rear	—	0.25 (0.010)
Wheel rim size	Front	J21 × 1.60	—
	Rear	J18 × 2.15	—
Tire size	Front	70/100-21 M/C 44P	—
	Rear	100/90-18 M/C 56P	—
Tire tread depth	Front	—	3.0 (0.12)
	Rear	—	3.0 (0.12)

SUSPENSION

Unit: mm (in)

ITEM	STANDARD	LIMIT
Front fork stroke	205 (8.1)	—
Front fork spring free length	—	561 (22.1)
Front fork oil level	180 (7.1)	—
Rear shock absorber spring pre-set length	231 (9.1)	—
Rear wheel travel	205 (8.1)	—
Swingarm pivot shaft runout	—	0.6 (0.02)

TIRE PRESSURE

COLD INFLATION TIRE PRESSURE	SOLO RIDING			DUAL RIDING		
	kPa	kgf/cm ²	psi	kPa	kgf/cm ²	psi
FRONT	150	1.50	22	150	1.50	22
REAR	175	1.75	25	200	2.00	29

FUEL + OIL

ITEM	SPECIFICATION	NOTE
Fuel type	Use unleaded gasoline with an octane rating of 87 AKI or higher. Do not use leaded gasoline. Unleaded gasoline containing up to 15% MTBE by volume may be used. Unleaded gasoline containing up to 10% ethanol by volume may be used. Unleaded gasoline containing up to 5% methanol by volume may be used if it also contains appropriate cosolvents and corrosion inhibitors.	
Fuel tank capacity	including reserve 12.5 L (3.3/2.7 US/Imp qt)	For California (E-33)
	12.0 L (3.2/2.6 US/Imp qt)	
	reserve 2.5 L (0.7/0.5 US/Imp qt)	
Engine oil type	SAE 10W-40, API SF/SG or SH/SJ with JASO MA	
Engine oil capacity	Change 850 ml (0.9/0.7 US/Imp qt)	
	Filter change 950 ml (1.0/0.8 US/Imp qt)	
	Overhaul 1 100 ml (1.2/1.0 US/Imp qt)	
Front fork oil type	Fork oil #10	
Front fork oil capacity (each leg)	309 ml (10.4/10.9 US/Imp oz)	
Brake fluid type	DOT 4	

TIGHTENING TORQUE

ENGINE

ITEM		N·m	kgf-m	lbf-ft
Cylinder head cover bolt		10	1.0	7.0
Camshaft sprocket bolt		11	1.1	8.0
Cylinder head nut	M8	27	2.7	19.5
Cylinder head nut	M6	10	1.0	7.0
Cylinder base nut		10	1.0	7.0
Starter clutch securing bolt		25	2.5	18.0
Cam drive chain tension adjuster bolt		7	0.7	5.0
Generator rotor nut		90	9.0	65.0
Crankcase bolt		11	1.1	8.0
Primary drive gear nut		50	5.0	36.0
Clutch cover bolt and generator cover bolt		10	1.0	7.0
Starter motor lead wire connecting bolt		2.5	0.25	1.8
Starter motor mounting bolt		10	1.0	7.0
Starter motor relay mounting screw		5.5	0.55	4.0
Clutch sleeve hub nut		50	5.0	36.0
Gearshift arm stopper		19	1.9	13.5
Engine oil drain plug		28	2.8	20.0
Oil filter cap nut and oil pump filter cap bolt		7	0.7	5.0
Engine sprocket bolt		25	2.5	18.0
Engine mounting bolt (Top side)		41	4.1	29.5
Engine mounting bolt (Front side)		88	8.8	63.5
Engine mounting bolt (Rear side)		10	1.0	7.0
Engine mounting bracket bolt		41	4.1	29.5
Exhaust pipe bolt		23	2.3	16.5
Muffler connection bolt		23	2.3	16.5
Muffler mounting bolt (Front side)		23	2.3	16.5
Muffler mounting bolt (Rear side)		26	2.6	19.0
Exhaust pipe cover nut		5.5	0.55	4.0
Muffler cover screw		3	0.3	2.0
Muffler drain plug		61	6.1	44.0
Stator coil bolt		4.5	0.45	3.5
Signal coil bolt		4.5	0.45	3.5
Throttle cable lock nut (Carburetor side)		4.5	0.45	3.5
Ignition coil mounting screw		4.5	0.45	3.5
Regulator/rectifier mounting bolt		9	0.9	6.5
Fuel valve mounting bolt		4.4	0.44	3.0

CHASSIS

ITEM	N-m	kgf-m	lbf-ft
Front axle nut	48	4.8	34.5
Front fork damper rod bolt	20	2.0	14.5
Front fork lower clamp bolt	30	3.0	21.5
Front fork upper clamp bolt	30	3.0	21.5
Steering stem head nut	90	9.0	65.0
Handlebar clamp bolt	23	2.3	16.5
Handlebar holder nut	45	4.5	32.5
Front brake master cylinder mounting bolt	10	1.0	7.0
Front brake lever pivot bolt	1	0.1	0.5
Front brake lever pivot bolt lock nut	6	0.6	4.5
Front brake caliper mounting bolt	26	2.6	19.0
Front brake pad mounting bolt	18	1.8	13.0
Front brake caliper axle bolt	23	2.3	16.5
Front brake hose union bolt	23	2.3	16.5
Air bleeder valve	8	0.8	6.0
Front brake disc bolt	23	2.3	16.5
Swingarm pivot nut	65	6.5	47.0
Front footrest bolt	85	8.5	61.5
Rear torque link nut	13	1.3	9.5
Rear shock absorber nut (Upper & lower)	60	6.0	43.5
Rear cushion lever center nut	72	7.2	52.0
Rear cushion lever nut	78	7.8	56.5
Rear axle nut	65	6.5	47.0
Rear sprocket bolt	27	2.7	19.5
Rear brake cam lever bolt	11	1.1	8.0
Rear brake pedal nut	13	1.3	9.5
Spoke nipple	4.5	0.45	3.5
Seat rail bolt	23	2.3	16.5
Clutch lever holder bolt	10	1.0	7.0
Clutch lever pivot bolt lock nut	6.5	0.65	4.5
Headlight cover screw	5.5	0.55	4.0
Speedometer mounting nut	2.5	0.25	2.0
Speedometer bracket mounting bolt	10	1.0	7.0
Pilot light box mounting screw	2	0.2	1.5
Pilot light box holder mounting screw	2	0.2	1.5
Speedometer cable nut	5	0.5	3.5
Speedometer cable screw	10	1.0	7.0